D-Link®

INCLUDES 2 POWERLINE HD ADAPTERS



POWERLINE HD ETHERNET STARTER KIT

INTERNET VIDEO, VOICE OVER ELECTRICAL WIRES

Up to 200Mbps speed. Video/voice distribution, broadband Internet over home's electrical wires



QUALITY OF SERVICE

Prioritized traffic for streaming video, on-line games, Internet phone, music



TOTAL SECURITY

Data encryption/Net ID to keep out intruders in building, VLAN isolation to protect home network from being tapped



USE EXISTING WIRING TO CREATE A HOME NETWORK

D-Link's PowerLine HD Ethernet Starter Kit DHP-301 is an ideal solution for connecting computers, HD media players, game consoles, and network attached storage to your home network. By simply attaching one adapter from your router into your existing electrical system, ¹ you can turn every power outlet into a possible network connection.

200Mbps TRANSMISSION OVER ELECTRICAL WIRES

D-Link's PowerLine HD is a new-generation power line network that provides easy-to-use technology for high-quality transfers of Internet video, music, games and voice through the conventional home power sockets. Delivering data transfer rates of up to 200Mbps, ² D-Link's PowerLine HD provides ample bandwidth, enabling digital home consumers to tap into the existing electrical wiring for extension of their home network.

EXPAND YOUR NETWORK WITHOUT RUNNING WIRES

D-Link's PowerLine HD Ethernet technology extends your network's range without drilling holes into walls by utilizing your home's existing electrical system. It is also ideal for homes or small offices where concrete walls, successive floors in multi-storied buildings, or other architectural impediments could inhibit a wireless signal. Connect multiple devices in the farthest corners of your home by attaching a switch or wireless access point to a D-Link PowerLine HD Ethernet Adapter. ¹

CONVENIENTLY CONNECT

D-Link's PowerLine HD Ethernet Adapter transmits data reliably by intelligently adapting to the strongest signal channels. Electrical currents don't interfere with the data network because electricity and data are transmitted at very different frequencies. In addition to a maximum throughput, D-Link's PowerLine HD includes a built-in Quality-of-Service (QoS) engine that prioritizes data packets in order to enhance HD video and audio streaming, intense online gaming, and VoIP calling. Plus, D-Link's Powerline HD implements 3DES encryption for securing your connection to help keep your data safe from intruders.

D-Link®


WHAT THIS PRODUCT DOES

D-Link's PowerLine HD Ethernet Starter Kit DHP-301 takes advantage of your home's existing electrical wiring 1 to create or extend a network. Turn every power outlet into a possible network connection to connect computers, digital media players, and game consoles throughout your house.

FAST TRANSMISSION ON HOME **POWER LINE**

D-Link's PowerLine HD uses the latest technology to deliver up to 200Mbps wired speed over a premise's existing electrical wires. ² This transmission speed provides ample bandwidth to stream high-quality video HDTV signals, while simultaneously providing high-speed Internet access throughout an entire home. With QoS support, D-Link's PowerLine HD does not compromise applications with real-time requirements, such as VoIP Internet phone and multiplayer on-line games, while allowing you to enjoy Internet TV and music in your living room.

YOUR NETWORK SETUP



POWERLINE HD

Power Prongs (Country Dependent) 2 To AC Wall Outlet

DHP-301



RJ-45 10/100BASE-TX Ethernet Ports

To TV Set-Top Box, Computers, Game Console, Network StorageDavice, Media player

TECHNICAL SPECIFICATIONS

STANDARD

IEEE 802.3 Ethernet/ 802.3u Fast Ethernet

POWER LINE INTERFACE

- Power prongs
- + Connector: country-dependent 3

ETHERNET INTERFACE

- Port: 10/100BASE-TX with auto MDI/
- Connector: RJ-45

POWER LINE MODULATION SCHEME **OFDM Symbol Modulation**

POWER LINE FREQUENCY BAND 2MHz to 32MHz

DATA RATE

- Power Line: 200Mbps (PHY rate) 2
- Ethernet: 10/100Mbps (auto-negotiation)

0 nS

- 802.1P Priority Queues standard (4 queues)
- Multi segment bursting

- + Mixed DES/3DES data encryption
- User-configurable Net ID (data encryption key)
- 802.10 VLAN Tagging (fixed value, not user-configurable)

CONFIGURATION/MANAGEMENT

- Windows-based Utility Program
- SNMP support (to manage encryption key)
- Telnet
- Remote software upgrade (FTPbased)

MINIMUM SYSTEM REQUIREMENTS (To run Utility Program)

- PC with 233MHz processor
- 64MB memory
- Windows XP SP2 or 2000 SP4
- + Ethernet adapter (100Mbps)

DIAGNOSTIC LED

- Power Line Link
- Power Line Activity
- + Ethernet Link/ Activity

AC INPLIT

100 to 240VAC, 50/60Hz, 160mA

DIMENSIONS

(Per adapter) 101 x 71 x 37 mm (3.98 x 2.79 x 1.46 inches)

WEIGHT

(Per adapter) 172 grams (0.379 lb)

OPERATION TEMPERATURE 0° to 40°C (32° to 104°F)

STORAGE TEMPERATURE

-20° to 70°C (-4° to 158°F)

OPERATION HUMIDITY

10% to 95% RH non-condensing

STORAGE HUMIDITY

10 to 90% RH non-condensing

EMC

- + FCC Part 15 Class B
- + CE

SAFETY UL

MTBF

100,000 hours or higher

- Power outlets and electrical wiring must all be part of the same electrical system. Additional PowerLine HD Ethernet adapters are required to add new devices to the network.
- ² Maximum throughput based on theoretical data rate. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, and network overhead, lower actual throughput rate.
- ³ Power prongs can differ from illustration. Power prong type depends on the country to which the product is shipped



D-Link Worldwide Offices									
U.S.A	TEL: 1-800-326-1688	FAX: 1-866-743-4905	Spain	TEL: 34 93 409 0770	FAX: 34 93 491 0795	Iran	TEL: 90-212-289-5659	FAX: 90-212-289-7606	
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223	Portugal	TEL: 351 21 8688493	FAX: 351 21 8622492	Pakistan	TEL: 92-21-454-8158	FAX: 92-21-453-5103	
Europe (U. K.)	TEL: 44-20-8955-9000	FAX: 44-20-8955-9001	Greece	TEL: 30 210 9914 512	FAX: 30 210 9916902	Israel	TEL: 972-9-9715700	FAX: 972-9-9715601	
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300	Czech Republic	TEL: 420 224 247 500	FAX: 420 224 234 967	Latin America	TEL: 56-2-5838-950	FAX: 56-2-5838953	
France	TEL: 33 1 30 23 86 88	FAX: 33 1 30 23 86 89	Hungary	TEL: 36 (0)1 461 30 00	FAX: 36 (0)1 461 30 04	Brazil	TEL: 55-11-2185-9300	FAX: 55-11-2185-9322	
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331	Poland	TEL: 48 (0)22 583 92 75	FAX: 48 (0)22 583 92 76	South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186	
Belgium & Luxembur	g TEL: 32 (0)2 517 7111	FAX: 32 (0)2 517 6500	Bulgaria	TEL: 359 2 958 22 42	FAX: 359 2 958 65 57	Russia	TEL: 7-495-744-0099	FAX: 7-495-744-0099	
Switzerland	TEL: 41 (0)1 832 11 00	FAX: 41 (0)1 832 11 01	Romania	TEL: 40(0)21 320 23 05	FAX: 40(0)21 320 23 07	Japan	TEL: 81-3-5781-0963	FAX: 81-3-5781-0965	
Austria	TEL: 43 (0)1 240 27 270	FAX: 43 (0)1 240 27 271	Singapore	TEL: 65-6774-6233	FAX: 65-6774-63225	Korea	TEL: 82-2-890-5491	FAX: 82-2-890-549	
Sweden	TEL: 46 (0)8 564 619 00	FAX: 46 (0)8 564 619 01	Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868	China	TEL: 86-10-58635800	FAX: 86-10-58635799	
Denmark	TEL: 45-43-969040	FAX: 45-43-424347	India	TEL: 91-22-2652 6696	FAX: 91-22-2652 8914	Taiwan	TEL: 886-2-6600-0123	FAX: 886-2-6600-3939	
Norway	TEL: 47 99 300 100	FAX: 47 22 30 90 85	Middle East (Dubai)	TEL: 971-4-391-6480	FAX: 971-4-390-8881	Headquarters	TEL: 886-2-6600-0123	FAX: 886-2-6600-9898	
Finland	TEL: 358-10 309 8840	FAX: 358-10 309 8841	Egypt	TEL: 202-291-9035	FAX: 202-291-9051				
to to	TEL 00 00 0000 0070	EAV 00 00 0000 1700	Total	TEL 00 010 000 F0F0	EAV 00 010 000 7000				