





802.11g Wireless Broadband Router

With Built-in 4-Port Switch

The D-Link AirPlusG DI-524 wireless router is the ideal networking solution for homes and small offices. This router combines the high-speed 802.11g wireless technology and robust firewall security features in providing broadband Internet connection to a small workgroup. It's an ideal device for those creating their first wireless networks, as well as for more advanced users looking for advanced network protection and content filtering.

High-Speed Wireless Speed

The DI-524 router offers a maximum wireless signal rate of up to 54Mbps through its wireless channels, allowing streaming videos and other high bandwidth applications such as on-line gaming and video clips to operate without the hassle of Ethernet cables. The ability to handle high bandwidth applications also makes streaming real time programs more enjoyable and more efficient.

Advanced Built-in Firewall

The DI-524's built-in firewall makes it more difficult for hackers to penetrate your network. Firewall features include functions to allow or disallow certain ports to be open for certain applications. Time scheduling can be applied to the firewall rules to have specific ports open at certain times and to be closed at other times. Features like content filtering, MAC filtering, URL blocking, and domain blocking are useful tools to prevent unwanted intruders from connecting to your network or browsing restricted sites.

Easy Setup and Secure Data Transfer

A simple, intelligent web-based setup wizard is provided with the DI-524 to allows users to quickly set up the router and connect computers to share a high-speed Internet connection, files, resources, games or just to communicate. Multiple wireless clients can also securely connect to the network using 64-bit or 128-bit WEP data encryption.

Integrated Ethernet Switch

An integrated 4-port switch allows ready connection of up to 4 computers. This saves you the cost of purchasing and installing a separate switch for network computer connections.

Key Features

- Remote router with 802.11g wireless LAN interface
- Cable/DSL modem Internet sharing
- Wireless LAN speed up to 54Mbps
- 10/100BASE-TX port for DSL/cable modem connection
- WAN port supports PPPoE for Internet dial-up mode
- 4 built-in 10/100BASE-TX switch ports with auto MDI/MDIX support
- Firewall features include NAT with VPN pass-through, MAC/IP/URL filtering, domain blocking and scheduling
- Web-based configuration with setup wizard for quick installation

Technical Specifications

Standards

- IEEE 802.11g
- IEEE 802.11b
- IEEE 802.3
- IEEE 802.3u

Wireless Modulation Technology

Orthogonal Frequency Division Multiplexing (OFDM)

Wireless Frequency Range

2.4GHz to 2.462GHz

Wireless Signal Rates

(With automatic fallback)

54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps, 5, 5Mbps, 2Mbps, 1Mbps

Wireless Receiver Sensitivity

- 54Mbps OFDM, 10% PER, -68dBm
- 48Mbps OFDM, 10% PER, -68dBm
- 36Mbps OFDM, 10% PER, -75dBm
- 24Mbps OFDM, 10% PER, -79dBm
- 18Mbps OFDM, 10% PER, -82dBm
- 12Mbps OFDM, 10% PER, -84dBm
- 11Mbps CCK, 8% PER, -82dBm
- 9Mbps OFDM, 10% PER, -87dBm
- 6Mbps OFDM, 10% PER, -88dBm
- 5.5Mbps CCK, 8% PER, -85dBm
- 2Mbps QPSK, 8% PER, -86dBm
- 1Mbps BPSK, 8% PER, -89dBm

Wireless Transmit Output Power

15dBm +/- 2dBm

External Antenna Type

Single detachable reverse SMA

Wireless Operating Range

- Indoors: up to 100 m
- Outdoors: up to 400 m
- * Environmental factors may adversely affect operating range

Security

- 802.1x user authentication support
- 64-, 128-WEP wireless data encryption
- WPA Wi-Fi Protected Access (WEP with TKIP, MIC, IV Expansion, Shared Key Authentication)

Firewall Features

- NAT (Network Address Translation) with VPN pass-through
- MAC address filtering
- IP address filtering
- URL filtering
- Domain blocking
- Scheduling

VPN Pass-Through/Multi-Sessions

- PPTP
- L2TP
- IPSec

Device Management

- Web-based Internet Explorer v.6 or Netscape Navigator v6 or other Java-enabled browsers
- DHCP Server and Client

Diagnostic LEDs

- Power
- Status
- WAN
- LAN (10/100Mbps)
- WLAN

2.4GHz Wireless Broadband Router

Physical & Environmental

Power Input

Through external power adapter

Dimensions

142 (L) x 109 (W) x 31 (H) mm

Weight

220 grams

Operating Temperature

0° to 55°C

Humidity

95% maximum (non-condensing)

Safety and Emissions

- FCC
- CE



Ordering Information

DI-524

802.11g Wireless Router With Built-in 4-Port Switch

D-Link[®]

ations subject to change inor notice. opeuncations subject to chang without prior notice. D-Link is a registered trademar and AirPlusG is a trademark of D-Link Corporation/D-Link System Inc. All other trademar belong to their proprietors.

TEL: 1-800-326-1688 TEL: 1-905-8295033 U.S.A Europe (U. K.) TEL: 44-20-8731-5555 France Netherlands Belgium Italy Sweden Denmark Norway Finland Spain Portugal

Czech Republic Hungary Singapore Australia Middle East (Dubai)

LatinA Brazil South Africa China

Greece

India

Turkey

Egypt Israel

TEL: 49-6196-77990 TEL: 33-1-30238688 TEL: 31-10-282-1445 TEL: 32(0)2-517-7111 TEL: 39-02-2900-0676 TEL: 46-(0)8564-61900 TEL: 45-43-969040 TEL: 47-23-897189 TEL: 358-9-2707 5080 TEL: 34-93-4090770 TEL: 351-21-8688493 TEL: 420-(603)-276-589 TEL: 41-(0)-1-832-11-00 TEL: 30-210-9914 512 TEL: 32-(0)2-517-7111 TEL: 48-(0)-22-583-92-75 TEL: 36-(0)-1-461-30-00 TEL: 65-6774-6233 TEL: 61-2-8899-1800 TEL: 91-022-26526696 TEL: 971-4-3916480 TEL: 90-212-289-56-59 TEL: 202-414-4295 TEL: 972-9-9715700 TEL: 56-2-232-3185 TEL: 55-11-218-59300

TEL: 27-12-665-2165

TEL: 7-095-744-0099 TEL: 86-10-58635800

TEL: 886-2-2910-2626 TEL: 886-2-2916-1600

FAX: 41(0)-1-832-11-01 FAX: 30-210-9916902 FAX: 32-(0)2-517-6500 FAX: 48-(0)-22-583-92-76 FAX: 36-(0)-1-461-30-09 FAX: 65-6774-6322 FAX: 61-2-8899-1868 FAX: 91-022-26528914 FAX: 971-4-3908881 FAX: 90-212-289-76-06 FAX: 202-415-6704 FAX: 972-9-9715601 FAX: 56-2-232-0923 FAX: 55-11-218-59322 FAX: 27-12-665-2186 FAX: 7-095-744-0099 #350 FAX: 86-10-58635799 FAX: 886-2-2910-1515

FAX: 886-2-2914-6299

FAX: 1-866-743-4905

FAX: 49-6196-7799300 FAX: 33-1-30238689

FAX: 31-10-282-1331

FAX: 32(0)2-517-6500

FAX: 39-02-2900-1723

FAX: 46-(0)8564-61901 FAX: 45-43-424347

FAX: 47-22-309085 FAX: 358-9-2707-5081

FAX: 34-93-4910795

FAX: 1-905-8295223 FAX: 44-20-8731-5511

Rev. 01 (Mar. 2005) Headquarters