

## 4-Port Wireless 108 G Print Server

### For 4 Multifunction Printers Sharing

- 4 USB Printer Connections
- Supports Scanning Function of Multifunction Printers
- Integrated 802.11g Wireless Interface
- Ethernet Connection to Wired Network
- Ideal for Office, School, Business Use

#### FEATURES

- 4 USB 2.0 Printer Ports
- Share Up to 4 USB Printers, Multifunction Printers
- Easy Control & Printing of Scanned Documents
- Built-in 802.11g Wireless Interface
- 10/100BASE-TX Ethernet Port Can Act as WLAN Bridge
- Supports TCP/IP, NetBEUI Operating Systems (Windows, Linux)
- Simple Web-Based Setup/Management of Print Jobs



The DPR-1260 wireless 108 G multifunction print server is a versatile multi-port print server ideal for office, school and business use. Providing 4 USB ports for 4 USB printer connections, this device give users the option of adding multiple printers, multifunction printers, or scanners to the network. With simple configuration and high wireless network speed, the DPR-1260 makes it easy to share multiple devices over the network and reduces the time required to send print jobs to the print server.

*Multifunction Printer Sharing.* Tested with a wide range of different printer models, the DPR-1260 offers a high level of compatibility. Printing a file on a network printer is transparent, and users can easily control the scanning of documents, photos directly from their computers. The multifunction printer's scanning function can be controlled over a wireless network. Users can share data through the memory card on the multifunction printer's slot, and print it through the same printer wirelessly. The DPR-1260 is compatible with a wide range of USB multifunction printers and scanners and is backward compatible with USB 1.1/1.0 printers.

*High-Speed Wireless Connection and Expandability.* The DPR-1260 offers wireless speed of up to 108Mbps Turbo mode from any computer equipped with 2.4GHz frequency band wireless interface, and an Ethernet port that can also serve as a wireless bridge. This provides wireless connectivity for any Ethernet-enabled device, such as a computer, Digital Video Recorder (DVR), or Network-Attached Storage (NAS) to the network printers.

*Simultaneous Operation of Connected Printers.* With 4 multifunction printer connections from a single device, the DPR-1260 is the perfect choice for environments where space or price is a concern. Equipped with a powerful CPU, large buffer size, high-speed USB ports and high-speed network data transfer, the DPR-1260 makes network operation fast. All shared devices attached to the DPR-1260 can print and scan at the same time, giving this multi-port print server a similar performance as 4 separate single-port print servers.

*Network Security and Multiple O.S. Support.* The DPR-1260 provides the necessary security for wireless users, using the user-selectable 64/128-bit industry-standard WEP (Wired Equivalent Privacy) data encryption and Wi-Fi Protected Access (WPA-PSK, WPA-EAP). It supports many network OS, including Windows and Linux, giving users the flexibility to install the print server regardless of the network environment.



## Technical Specifications

### Standards

- IEEE 802.11g
- IEEE 802.11b
- IEEE 802.3
- IEEE 1284
- USB 2.0

### Ports

- 4 USB 2.0 ports
- 10/100BASE-TX Ethernet LAN port

### Wireless Signal Rates

(With Automatic Fallback)

108, 54, 48, 36, 24, 18, 12, 11, 9, 6, 5.5, 2, 1Mbps

### Wireless Frequency Range

2.4GHz to 2.462GHz

### Wireless Transmit Power

15dBm +/- 2dBm

### External Antenna Type

Detachable antenna with reverse SMA connector

### Modulation Technology

- Orthogonal Frequency Division Multiplexing (OFDM)
- Complementary Code Keying (CCK)

### Security

- 64/128-bit WEP data encryption
- Wi-Fi Protected Access (WPA-PSK, WPA-EAP)

### Transport Protocols

- TCP/IP
- NetBEUI

### Device Management

- Internet Explorer v.6 or later; or other Java-enabled browsers
- DHCP server and client

### Diagnostic LEDs

- Power
- Ethernet Link/Activity
- WLAN
- USB (1 to 4)

## Physical & Environmental

### Power Input

Through external power adapter

### Operating Temperature

0° to 55°C (32° to 131°F)

### Operating Humidity

95% maximum (non-condensing)

### Dimensions

148 x 114 x 31 mm  
(5.59 x 1.22 x 4.29 inches)

### Weight

233.8 grams (0.46 lbs)

### Certifications

- FCC
- CE
- C-Tick
- IC
- CSA



## D-Link Worldwide Offices

<b>U.S.A.</b>	TEL: 1-800-326-1688	FAX: 1-866-743-4905	<b>Luxemburg</b>	TEL: 32-(0)2-517-7111	FAX: 32-(0)2-517-6500
<b>Canada</b>	TEL: 1-905-8295033	FAX: 1-905-8295223	<b>Poland</b>	TEL: 48-(0)-22-583-92-75	FAX: 48-(0)-22-583-92-76
<b>Europe (U. K.)</b>	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511	<b>Hungary</b>	TEL: 36-(0)-1-461-30-00	FAX: 36-(0)-1-461-30-09
<b>Germany</b>	TEL: 49-6196-77990	FAX: 49-6196-7799300	<b>Singapore</b>	TEL: 65-6774-6233	FAX: 65-6774-6322
<b>France</b>	TEL: 33-1-30238688	FAX: 33-1-30238689	<b>Australia</b>	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
<b>Netherlands</b>	TEL: 31-10-282-1445	FAX: 31-10-282-1331	<b>India</b>	TEL: 91-022-26526696	FAX: 91-022-26528914
<b>Belgium</b>	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500	<b>Middle East (Dubai)</b>	TEL: 971-4-3916480	FAX: 971-4-3908881
<b>Italy</b>	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	<b>Turkey</b>	TEL: 90-212-289-56-59	FAX: 90-212-289-76-06
<b>Sweden</b>	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901	<b>Egypt</b>	TEL: 202-414-4295	FAX: 202-415-6704
<b>Denmark</b>	TEL: 45-43-969040	FAX: 45-43-424347	<b>Israel</b>	TEL: 972-9-9715700	FAX: 972-9-9715601
<b>Norway</b>	TEL: 47-99-300-100	FAX: 47-22-309580	<b>LatinAmerica</b>	TEL: 56-2-232-3185	FAX: 56-2-232-0923
<b>Finland</b>	TEL: 358-9-2707 5080	FAX: 358-9-2707-5081	<b>Brazil</b>	TEL: 55-11-218-59300	FAX: 55-11-218-59322
<b>Spain</b>	TEL: 34-93-4090770	FAX: 34-93-4910795	<b>South Africa</b>	TEL: 27-12-665-2165	FAX: 27-12-665-2186
<b>Portugal</b>	TEL: 351-21-8688493		<b>Russia</b>	TEL: 7-495-744-0099	FAX: 7-495-744-0099 #350
<b>Czech Republic</b>	TEL: 420-(603)-276-589		<b>Japan</b>	TEL: 81-3-5781-0963	FAX: 81-3-5781-0965
<b>Switzerland</b>	TEL: 41-(0)-1-832-11-00	FAX: 41(0)-1-832-11-01	<b>China</b>	TEL: 86-10-58635800	FAX: 86-10-58635799
<b>Greece</b>	TEL: 30-210-9914 512	FAX: 30-210-9916902	<b>Taiwan</b>	TEL: 886-2-6600-0123	FAX: 886-2-6600-8168
			<b>Headquarters</b>	TEL: 886-2-6600-0123	FAX: 886-2-6600-9898