



D-View

D-View SNMP Network Management System

D-View SNMP Network Management System is a comprehensive standards-based management tool designed to centrally manage critical network characteristics such as availability, responsiveness, resilience and security in a consistent way. Flexible and versatile, this software accommodates a wide range of new D-Link and third-party devices, including wireless bridges and access points, multi-layer switches, remote routers, and multi-tenant broadband CO devices. D-View provides useful tools to allow you to effectively manage device configurations, fault tolerance, performance, security and accounting services.

Modular Architecture

D-View is organized into a vendor-independent platform and user plug-in modules. The platform consists of five main components, namely the Alarm/Trap Manager, Discovery/Parsing, MIB utilities, Internet tools, and the *User Account Manager. Plug-in modules are for the devices that you want to manage. When you select a device to manage, D-View will look for that device's plug-in module and display it on the screen.

Managing Third-party Devices

You can also manage non-D-Link SNMP devices without plug-in modules. D-View provides a MIB compiler for you to compile MIB files from the vendor of the device into a System recognized format, then loads it into a database.

The compiler can communicate with your network device to get the current values or to set a new values for the MIB objects of your interest. All MIBs are converted into a graphic tree view, with which can use the MIB Browser to manage the device. D-view's Module Wizard will look for the compiled MIB files then organize and display the contents on the screen for you.

Microsoft Access Format Database

MIB contents in the database generated by the MIB compiler are organized according to the Microsoft Access format. This enhances the integration of your environment, while giving you the options of editing your database using D-View or the familiar Microsoft Access software.

Features

- Cost-effective, easy-to-use SNMP management software for management of workgroup/departmental networks
- Structured into an independent platform and plug-in modules for D-Link devices
- MIB compiler & MIB Browser allow easy management of third-party devices under the same platform
- Layer 3 utilities to manage Layer 3 switches and advanced routers *
- SNMP V3 support for major MIBs *
- Topology creation program useful for network design and layout planning
- Multiple views to view objects in Ethernet domain by "tree"
- Trap/Alarm notification by e-mail
- Accounts information functions & billing system *
- Database in familiar Microsoft Access format

* Supported in Professional Version only;

Versatile Features

D-View incorporates the following powerful features:

- Layer 3 utilities including IP Forwarding, RIP 2, OSPF, IP MRoute, DVMRP and PIM functions to accommodate the increasing presence of Layer 3 switches and advanced routers in enterprise networks *.
- DIAP (D-Link Private Discover Protocol) used in D-Link SOHO broadband routers eliminates the need for additional utility to administer these devices.
- Accounts information functions to maintain client records.
- Topology creation program to create diagrams and schematics useful for network design and layout planning.
- SNMP V3 support for major MIBs including MIB II, IF-MIB (RFC2233), Entity MIB (RFC2737), Bridge 802.1D (RFC1493), RMON, 802.1P (RFC2674), and 802.1Q (RFC2674). *
- Trap/Alarm notification by e-mail.
- Multiple views for platform to let you view objects in the Ethernet domain by tree view. At the same time you can have a list view display open. Additionally you can create a topology domain in the same workspace to make network management more convenient.
- Powerful, easy-to-use MIB Compiler and Browser for use independent of D-View or with the D-View software. This makes network management more effective and efficient.

User Account Management *

User account management can be used with devices like wireless broadband gateways and multi-tenant broadband switches to provide connection to paying customers. This account system can bundle customer equipment just like the telephone system. As with telephone numbers, you can manage customers by means of equipment management.

Billing System *

A simple billing system offers services in connection with user account management. This billing system has the following features:

- Assignment of account with personal authorization IP address for each client.
- Generation of statements with different schedules for different groups of clients.

- Detection of abnormal usage for clients. *
- Assignment of custom taxes to service charges. *
- Credit adjustment function to let you insert credit records manually and give credit for wrong or misdialed work. *
- Late fee assessment function.*
- Real-time reporting, including current client summary, credit limit status report, and payment report.*


Tree View

To let you easily view your entire network, D-View groups it into major domains extending from the Root. The major domains for the default setup are Ethernet, Company Group, Favorites and Topology. The Favorites Group is a vacant domain available as a convenient means of tracing devices that require frequent monitoring, which can be arranged into sub-domains as needed. In the Company Group, D-View can automatically recognize up to 33 third-party device manufacturers and group them into sub-domains according to manufacturers. The "tree" in this panel or any domain can be expanded or contracted to view the contents of any group.

Topology Diagram & Auto Discovery

You can create a topology diagram to graphically represent planned or existing networks to aid network design. You can use live device icons copied from any domain or create new symbols and incorporate them in the diagram. You can further customize your diagram with selected icons and bitmap files used for the background.

When a topology map is opened, D-View can discover the devices on your network and display their icons on the map. D-View can recognize a device's standard (SNMP or not), its type (router, switch or others), its network domain, then categorizes and groups all devices accordingly. D-View employs multiple discover rules to shorten and speed up the discover time. The protocols used in polling to discover the devices are SNMP and ICMP, in addition to D-Link's DIAP protocol used in association with D-Link devices. For remote devices such as routers, traps are sent to obtain status information.



System Requirements

- CPU: 550 Mhz or above
- DRAM: 256MB
- Hard drive available space: 100MB
- Ethernet adapter: 10/100BASE-TX
- Operating System: Windows 2000 or Windows XP
- Access 2000 software

MIB Utilities

- Device SNMP Configuration *
- MIB II Information and Statistics Windows
- IF MIB Information Tables
- Entity MIB Information Tables
- Bridge 802.1d Information and Port Configuration Table
- Spanning Tree Information and Port Configuration Table
- Transparent Bridge Forwarding and Static Filter Tables and Port Counter
- RMON Statistics, History and Event Windows
- 802.1p Priority Configuration including GMRP and GARP *
- 802.1Q VLAN Information and Configuration including Forwarding/Filtering and Unicast/Multicast Configuration *
- Port VLAN Traffic Statistics *
- Layer 3 Utilities including IP Forwarding, RIP2, OSPF, IP Multicast, DVMRP and PIM Configuration *
- SNMP Configuration *

Configuration Management Functions

- MIB utilities
- MIB Compiler
- MIB Browser
- Web configuration
- DIAP tools
- TFTP file transfer
- Bootp
- Ping

Fault Management Functions

- Trap log
- Trap filter
- Trap mail
- Trap editor
- Message log
- Ping
- Alarm mail interval

Performance Management Functions

- RMON
- 802.1d bridge
- Port counter
- VLAN *
- Traffic statistics
- RIP-2 routing *
- DVMRP interface table *
- IP MROUTE *

Security Management Functions *

SNMP v3 covers security functions such as packet encryption/decryption, user levels for different classes of access right, MPD (RFC 2572), TARGET (RFC 2573), USM (RFC 2574) user-based security level, VACM (RFC 2575) view-based access control.

- Device SNMP configuration
- SNMP v3 configuration

Accounting Management Functions *

- Client information update
- Freeze/unfreeze client connection
- Client record query
- Client On-line query
- Client abnormal situation
- Device utilization
- Pay Rate Configuration

* Functions available in Professional Version only

Supported D-Link Devices

- Managed 10/100Mbps & Gigabit L2, L3 switches
- Remote routers
- Wireless Access Points & bridges
- VDSL switches

Supported 3rd-Party Devices

- ATiHub
- Cisco 760 Router, 1600 Router, 2500 Router, Catalyst 2900 series
- HP 28xxA switch, Switch 200, Switch 16, Router 200/400/ 600 series, 286xx Hub, J2355A
- Nortel/Wellfleet Router
- Microsoft NT



Ordering Information

DS-510

D-View SNMP Network Management Program

Please specify your order as follows:

DS-510P

Professional version

DS-510P/CN

Professional version (Simplified Chinese)

DS-510S

Standard version

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A.	TEL: 1-949-788-0805	FAX: 1-949-753-7033
Canada	TEL: 1-905-829-5033	FAX: 1-905-829-5095
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
U.K.	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-61- 96779900	FAX: 49-61-967799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Benelux	TEL: 31-10-204-5740	FAX: 31-10-204-5880
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795
Sweden	TEL: 46-(0)8-564-61900	FAX: 46-(0)8-564-61901
Norway	TEL: 47-22-991890	FAX: 47-22-205700
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Finland	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
China	TEL: 86-010-8518-2533	FAX: 86-010-8518-2250
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914
Middle East	TEL: 202-6244615	FAX: 202-6244583
South America	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brazil	TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
South Africa	TEL: 27(0)126652165	FAX: 27(0)126652186
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE
Rev. 02 (Jan. 2003)
Printed in Taiwan