How to change ADSL Username and Password in your modem router

This document details how to change ADSL Username and Password settings stored in your modem

Step 2. When prompted type in the Username and Password, enter the validation code displayed on your page and then click on the "Log In" button.

If you have not changed the password for the modem administration, the factory settings are:

Username: admin

Password: admin

D-Link ADSL Router ×	
← → C ⋒ 192.168.1.1/index.html	० 😪 🥥 🙆 😢 😫 😑
Product Page: DSL-2642B	Firmware Version: AU_2.10
D-Link	
LOGIN	
Welcome to DSL-2642B Web Management	
Username : admin	
Password :	
Login	
BROADBAND	
Copyright © 2008-2010 D-Link Systems, Inc	G.

If you cannot recall the password you assigned to your modem you will need to reset the modem to factory defaults by pressing the reset button for 10 seconds. Please note that this will revert all the settings in the modem to factory settings and you will have to reconfigure it with your Internet settings and Wireless security. Make sure you have your Internet account details (given by your Internet Provider) handy. Step 3.After logging in you will be presented with the modem's configuration pages.Please click on [Setup] tab, and then click on [Internet Setup]:

D-Link A	DSL Router ×										
(← → C	192.16	8.1.1/index.ht	ml						Ģ,	☆ 🧿 🖻 🌘) 🔣 😑
Produ	ıct Page: DSL-2642E	3								Firmware Version	n: AU_2.10
D)-Linl	C									
	DSL-2642B	SETUP		ADVANCED	MA	INTENAN	ICE	ST/	ATUS	HEL	р
Winne		INTERNET S	ЕТИР							Helpful Hint	s
Intern	net Setup	Wide Area No	atwork (WAN) Se	anvice Setun						When config router to acc	uring the less the
	Notwork	Choose Add,	or Remove to co	infigure a WAN se	ervice over	a selected	interface.			choose the c	sure to orrect
Time	and Date									the list below	/,
Logou	it	WAN CONFI	GURATION							Please take o entering you	are when
		Intorfaco	Description	Tuno Jamp	NAT	Firowall	TDv6	MID		username ar password as	nd s these are
		ppp0	pppoe_0_8_35	PPPoE Disabled	d Enabled	Enabled	Disabled	Disabled	1	case sensitive majority of co	e. The onnection
										incorrect use password combinations	rname or
					Add					Note: Be sure	e to restart
										the router for Internet Sett effect.	r the new ting to take
										More	
BR	OADBAND										
			Cop	oyright © 2008-20)10 D-Link S	ystems, In	с.				



Step 4. Click on the **Edit** button (looks like a notepad):

Step 5.	Scroll down the page to the [PPP Configuration] se	ection:
Step 5.	Seron down the page to the [111 comgaration] se	

D-Link ADSL Router ×					
← → C ☆ 192.168.1.1/index.html		€☆	0	🕖 🚼 😑	
+ - C A 192.168.1.1/index.html PPP ConFIGURATION PPP ConFIGURATION PPP Username: PPP Username: PPP Password: PPPOE Service Name: Authentication Method: Enable NAT: Enable Fullcone NAT: Enable Fullcone NAT: Enable Firewall: Dial on demand (with idle timeout timer): Use Static IPv4 Address:	username AUTO 		2		
					-

Step 6. Please type in your NEW account details as given by you Internet Service Provider:

- In the "PPP Username" field type in your new username given by your Internet Service Provider
- In the "PPP Password" field type in your new password given by your Internet Service Provider

Step 7. Click on the APPLY button at the bottom of the page:

D-Link ADSL Router	×	
← → C ff 🗅:	192.168.1.1/index.html	@ ☆ 🙆 🙆 😫 ≡
	 ● Obtain DNS info from a WAN interface: WAN Interface selected: pppoe_0_8_35/ppp0 ▼ ● Use the following Static DNS IP address: Primary DNS server: Secondary DNS server: 	
BROADBAI	םר	
	Copyright © 2008-2010 D-Link Systems, Inc.	

Now follow these steps to restart the modem and verify connection to your Internet Provider.

	108.1.1/IIIdex.ittiii	
Product Page: DSL-264	28	Firmware Version: AU_2
D-Lin	1 ¢	
DSL-2642B	SETUP ADVANCED MAINTENANCE STATU	S HELP
System	SYSTEM REBOOT	Helpful Hints
Firmware Update		This page allows you reboot your router d
Access Controls	Click the button below to reboot the router.	save your router
Diagnostics	Reboot	your computer as a
System Log		have to reset your
Logout	SYSTEM BACKUP SETTINGS	settings. You will be
	Back up DSL Router configurations. You may save your router configurations to a file on your f Note: Please always save configuration file first before viewing it. Backup Settings	PC. previously saved configuration file. There is also a funct to allow you to rese your router to facto defuilt sottimer.
		Resetting your route
	SYSTEM UPDATE SETTINGS	will delete your curre
	Update DSL Router settings. You may update your router settings using your saved files.	More

Step 8. Click on the [Maintenance] menu and then on the [Reboot] button.

Step 9.After your modem reboots, log into it again and check the [Status] page.Please wait 1-2 minutes and your modem should report Connection Status as Connected.

INTERNET	INFO						
Internet C	onnection:	pppoe_atm0	•				
IPV4 Conn	ection Statu	s:			CONNECT	ED	
IPV4 Default Gateway: ppp0							
IPV4 Preferred DNS Server:					203.12.160.35		
IPV4 Alternate DNS Server:			203.12.10	203.12.160.36			
Interface	Description	Link Type	IGMP	QoS	Status	IP Address	
0000	pppoe_atm0	PPPoF	Enabled	Disabled	Connected	110.175.245.250	