How to change ADSL Username and Password in your modem router

This document details how to change ADSL Username and Password settings stored in your modem

Step 1. Open your Internet Browser and in the address field type in <u>http://192.168.1.1</u>.

| 192.168.1.1/login.htm × | | | | | | | | | |
|--|-----------------------------|-------------|--|---|--|--|--|--|--|
| (← → C fi | 🗋 192.168.1.1/log | gin.htm | ☆ 🙆 🙆 😫 | | | | | | |
| Product Page : Du | ualband Wireless N750 Moder | n Router | Firmware Version:2.00.01 Build Timestamp:06272013 Language: en | - | | | | | |
| | - | | | | | | | | |
| D - | Link | | | | | | | | |
| | | | | | | | | | |
| | LOGIN | | | | | | | | |
| | Login in to the router | | | | | | | | |
| | | User Name : | jadmin | | | | | | |
| | | Password : | Jerrin . | | | | | | |
| | | | Logit | | | | | | |
| BRÖADBAND | | | | | | | | | |
| Copyright © 2012-2013 D-Link Systems, Inc. | | | | | | | | | |

Step 2. When prompted type in the Username and Password then click on the "Log In" button. If you have not changed the password for the modem administration, the factory settings are:

Username: admin Password: admin

Step 3. After logging in you will be presented with the modem's configuration pages. Please click on [**Setup**] tab, and then click on [**Wan Setup**]:

| | | | | | | | x | |
|---|---------------------------|---------------------------------------|--|--|--------|------|---|--|
| | Dualband Wireless | × // UC/VI | | | -) | | | |
| | ← → C' fi | 192.168.1.1/login.htm | | ☆ 🙆 🙆 🚼 ☰ | | | | |
| | Product Page : Dualband V | Wireless N750 Modem Router | Firmware | Firmware Version : 2.00.01 Build Timestamp : 06272013 Language : 🛛 🗨 🗲 | | | | |
| | | | | | | | | |
| | D-T i | n1/* | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | DSL-2870B | SETUP ADVA | NCED MAINT | ENANCE | STATUS | HELP | | |
| | Dinzard | | Helpful Hints | | | | | |
| C | WAN Setup | input all the settings | Here you can quickly setup your WAN connection. | | | | | |
| | Press. | · · · · · · · · · · · · · · · · · · · | These details should have been provide by your ISP | | | | | |
| | Wireless 2.4G Setup | | | (Internet Service Provider) Often you will received a |). | | | |
| | Wireless 5G Setup | OPERATING MODE bundle pack with the | | | | | | |
| | LAN Setup | Current Mode | | information. | | | | |
| | Time and Date | | (NBN/UFB Mod | e) | More | | | |
| | | | | | | | | |
| | Mydiink Seturigs | Interface | : PVC1 V | | | | | |
| | Offline | Country | | | | | | |
| | Ŭ | ISP | : (Click to Select) | | | | | |
| | Logout Reboot | ogout Reboot VPI: 8 | | | | | | |
| | | VCI | : 35 | | | | | |
| | | Encapsulation | : LLC 🔽 | | | | | |
| | | QoS | : | | | | | |
| | | WAN Type | : Default | | - | | | |
| | | Enable Virtual Circuit | : 🗸 | | | | - | |

Step 4. Scroll down to the **WAN** section of the page.

In the **Username** field type in the username as given by your Internet Provider.

In the **Password** field type in the password as given by your Internet Provider. Re-type your password in the **Confirm Password** field.



Step 5. Click on the Apply button.

Step 6. Click on the Reboot button and wait until your modem router reboots and re-connects with the new username and password.

