

Air Xpert™ 802.11 **AG**

Dualband



— DWL-AG520

Up to
5X
Faster

Up to
54
Mbps
in A or G!

Powerful antenna with extension antenna cable allows you to adjust the angle to get the best transmission/reception range.

802.11a/g Tri-Mode Dualband Wireless PCI Card

The D-Link Air Xpert™ DWL-AG520 wireless PCI card is a high-performance, versatile and necessary desktop PC networking solution for companies that need to quickly expand or reconfigure their wireless networks as their organization grows. This tri-mode, dualband network card inserts into your desktop PC to provide you a versatile way to wirelessly connect to any one of three available wireless networks -- 802.11b and the newer, faster 802.11g and 802.11a that operate in two discrete, non-interfering frequency bands, 2.4GHz and 5GHz.

Easiest Way to Expand

If you're a network administrator, the versatile 802.11a/b/g-compatible DWL-AG520 card gives you an immediate way to expand to your existing 802.11b network and protect your overall wireless network investment. By installing DWL-AG520 network cards in desktops throughout your organization your employees can access wireless Access Points and routers from their desktop PCs. And as your company expands or reorganizes you won't have to keep pulling and plugging Ethernet cables because no matter where the workstation is relocated, it's still connected to the network.

End-to-End Wireless Solution

When you add an 802.11a/b/g access point (D-Link Air Xpert DWL-7000AP) or router (D-Link Air Xpert DI-774), to your wireless network, you will have an end-to-end wireless solution capable of handling up to four times the user load of your current 802.11b network.

54Mbps Dualband High Speed

In addition to its compatibility with earlier 802.11b networks, the DWL-AG520 offers the robust speed, up to 54Mbps, of the newer 802.11g and 802.11a standards, so everyone can work faster and more efficiently. In addition to the 2.4GHz frequency band operated by 802.11b and g, the 5GHz band used by 802.11a also offers a way to quickly transfer data in a frequency range that does not experience interference or interruptions from cordless phones, microwave ovens and other devices utilizing the 2.4GHz frequency.

WPA Enhanced Security

Wi-Fi™ Protected Access in the DWL-AG520 provide the necessary security protocols and tools, so employees can communicate with colleagues confidentially, access sensitive company information or send data that is dynamically encrypted as it's sent. Wi-Fi™ Protected Access lets you authorize and identify users based on a secret key that changes automatically at a regular interval. Used in conjunction with a RADIUS server, WPA uses TKIP (Temporal Key Integrity Protocol) to change the temporal key every 10,000 packets. This insures much greater security than the standard WEP security, which requires the keys to be changed manually.

802.1x Authentication

The DWL-AG520 supports 802.1x authentication for protection against network intrusion. Used in conjunction with a RADIUS server, this function provides a means to verify the identity of the client before an access to the network is granted.

Pre-Shared Key

This function brings a lot of convenience (when used in conjunction with other 802.11g products) for users that do not incorporate a RADIUS server in their networks. Utilizing the Pre Shared Key mode of WPA, the DWL-AG520 will obtain a new security key every time it connects to the 802.11g network. You only need to input your encryption information once in the configuration menu. With the DWL-AG520, you will automatically receive a new key every time you connect, doing away with the inconvenience of manual WEP key input.

Features

- 802.11a/g industry standard
- Dual 5GHz and 2.4GHz frequency bands
- Up to 54Mbps network data transfer rate on both frequency bands, 5 times faster than 802.11b
- Strong 64/128-bit WEP data encryption security
- Compatible with existing 802.11b wireless devices
- Advanced security with WPA, 802.1x authentication, TKIP and Pre-Shared Key function support
- Powerful integrated antenna provides 100-meter indoor, 400-meter outdoor operation range
- Easy configuration, plug-and-play installation
- Runs Windows 98 SE, 2000, ME, XP

DWL-AG520

Technical Specifications

Technical Specifications

Standards

- IEEE 802.11a
- IEEE 802.11b
- IEEE 802.11g

Bus Type

- PCI 2.2
- PCI 32-bit interface

Media Access Control

CSMA/CA with ACK

Data Rates

(With automatic fallback)

54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps

Modulation Technology

- Orthogonal Frequency Division Multiplexing (OFDM)
- Complementary Code Keying (CCK)
- Direct Sequence Spread Spectrum (DSSS)

Frequency Range

- 2.4GHz to 2.5GHz
- 5.15GHz to 5.875GHz*

* Software configurable as allowable frequency will vary from country to country in the European region.

Transmit Output Power

15 dBm +/- 2dBm

Receiver Sensitivity

- 54Mbps OFDM, 10% PER, -72dBm
- 48Mbps OFDM, 10% PER, -75dBm
- 36Mbps OFDM, 10% PER, -78dBm
- 24Mbps OFDM, 10% PER, -84dBm
- 18Mbps OFDM, 10% PER, -87dBm
- 12Mbps OFDM, 10% PER, -88dBm
- 11Mbps CCK, 8% PER, -88dBm
- 9Mbps OFDM, 10% PER, -89dBm
- 6Mbps OFDM, 10% PER, -90dBm
- 5.5Mbps CCK, 8% PER, -91dBm
- 2Mbps QPSK, 8% PER, -91dBm
- 1Mbps BPSK, 8% PER, -92dBm

Antenna

2dBi - 4dBi Gain omni-directional dipole antenna

Operation Range

- Indoors: up to 100 meters (328 feet)*
- Outdoors: up to 400 meters (1,312 feet)*

* Environmental factors may adversely affect range

Security

- 64/128-WEP data encryption
- 802.1x authentication
- WPA (Wi-Fi™ Protected Access): 802.1x, Pre Share Key, WEP, TKIP, AES

Physical & Environmental

Dimensions

133 (L) x 120 (W) x 22 (H) mm (5.24 x 4.72 x 0.87 inches)

Weight

63 grams (0.14 lb.)

Operating Voltage

5 VDC +/- 10%

Operating Temperature

0° - 45°C

Storage Temperature

-10° - 60°C

Humidity

95% maximum (non-condensing)

5GHz & 2.4 GHz Wireless LAN

EMI Certification

- FCC Class B
- CE Class B

O.S. Support

Windows 98 SE, ME, 2000, XP



Ordering Information

DWL-AG520

802.11a/g Wireless LAN PCI Card

Please specify your order as follows:

DWL-AG520/EU

For UK, Ireland, Denmark, Germany, Iceland, Finland, Netherlands, Norway, Sweden, Poland, Slovenia, Luxembourg, South Africa

DWL-AG520/FR

For France

DWL-AG520/CN

For China (China packaging)

DWL-AG520/AU

For Australia

DWL-AG520/CA

For Canada

DWL-AG520/SG

For Singapore

DWL-AG520/T

For Taiwan

DWL-AG520/LA

For Latin America

DWL-AG520/ME

For the Middle East



Specifications subject to change without prior notice.
D-Link is a registered trademark and AirXpert is a trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A

Canada

Europe

Germany

France

Benelux

Italy

Iberia

Sweden

Norway

Denmark

Finland

Singapore

Australia

Japan

China

India

Egypt

UAE

Turkey

Israel

Chile

Brasil

South Africa

Russia

Taiwan

D-Link Corp.

TEL: 1-949-788-0805

TEL: 1-905-8295033

TEL: 44-20-8731-5555

TEL: 49-6196-77990

TEL: 33-1-30238688

TEL: 31-10-2045740

TEL: 39-2-2900-0676

TEL: 34-93-4090770

TEL: 46-(0)8564-61900

TEL: 47-22-309075

TEL: 45-43-969040

TEL: 358-9-2707-5080

TEL: 65-6774-6233

TEL: 61-2-8899-1800

TEL: 81-3-5434-9678

TEL: 86-10-8518-2533

TEL: 91-22-652-6696

TEL: 202-62-44615

TEL: 971-4-3916480

TEL: 90-212-335-2525

TEL: 972-9-9715700

TEL: 56-2-232-3185

TEL: 55-11-3094-2910

TEL: 27(0)1266-52165

TEL: 7-095-737-3389

TEL: 886-2-2910-2626

TEL: 886-2-2916-1600

FAX: 1-949-753-7033

FAX: 1-905-8295095

FAX: 44-20-8731-5511

FAX: 49-6196-7799300

FAX: 33-1-30238689

FAX: 31-10-2045880

FAX: 39-2-2900-1723

FAX: 34-93-4910795

FAX: 46-(0)8564-61901

FAX: 47-22-309085

FAX: 45-43-424347

FAX: 358-9-2707-5081

FAX: 65-6774-6322

FAX: 61-2-8899-1868

FAX: 81-3-5434-9868

FAX: 86-10-8518-2250

FAX: 91-22-652-8914

FAX: 202-62-44583

FAX: 971-4-3908881

FAX: 90-212-335-2500

FAX: 972-9-971-5601

FAX: 56-2-232-0923

FAX: 55-11-3094-2921

FAX: 27(0)1266-52186

FAX: 7-095-737-3390

FAX: 886-2-2910-1515

FAX: 886-2-2914-6299



RECYCLABLE

Rev. 02 (Jul. 2003)