MAC OS 9.x

If you have not done so yet, connect the USB ADSL modem to the computer using the proper USB device cable. Connect the DSL line to the USB ADSL modem, too.

TCP/IP settings are set up automatically during the software installation process. The following procedure may be used to change TCP/IP settings, if necessary.

Click on the Apple icon ([≤]), then select Control Panels
→ Modem

1	Modem				
Connect via:	Internal M	odem			
— Setup ——				۱ ا	
Modem :	ADSL USB Modem				
Sound :	🔘 On	🖲 Off			
Dialing:	🖲 Tone	🔘 Pulse			
	☑ Ignore dial tone				
0					

2. Make sure that the *ADSL USB Modem* appears in the **Modem:** drop-down list. You can modify the dialup

settings such as dialing sound and type.

- Close the "Modem" window (click on the top left corner). You will be prompted to save the current configuration. Click Save.
- Next, click again on the Apple icon ([≤]), and then select Control Panels → TCP/IP.
- 5. The "TCP/IP" window will appear.

		TCP/IP
	Connect via:	PPP 😫
	Configure :	Using PPP Server 🗢
	IP Address:	< will be supplied by server >
	Subnet mask :	< will be supplied by server >
	Router address:	< will be supplied by server >
	Name server addr.:	Search domains :
0		

- Make sure that **PPP** is selected in the Connect via: drop-down list.
- The Configure: drop-down list should show Using DHCP Server.
 - 6. Close the "TCP/IP" window. You will be prompted to save the current configuration. Click **Save**.
 - 7. Click on the **Apple** icon (\clubsuit), and then select **Control Panels** \rightarrow **Remote Access**.
 - 8. The "Remote Access" window lets you set up the remote

🗆 🔤 Remote Access 🔤 🗧 🗧
▽ Setup
🖲 Registered User 🕥 Guest
Name : username
Password:
Save password
Number: 88
- Status
ldle.
Options Connect

login parameters.

Note: If you do not see the *Name* and *Password* fields, click on the

small triangle to the left of the word **Setup**.

- Enter your userid in the Name field.
- Type in your password in the *Password* field.
- Choose whether or not to have your password saved by checking or unchecking the *Save Password* check box.
- Enter any number in the *Number* field.
- You may wish to use the **Options** button to set up some additional connection and protocol settings, or accept the default. Click **OK** when done with the "Options" window.

9. Close the "Remote Access" window. You will be prompted to save the current configuration. Click **Save**.

MAC OS X

If you have not done so yet, connect the USB ADSL modem to the computer using the proper USB device cable. Connect the DSL line to the USB ADSL modem, too.

TCP/IP settings are set up automatically during the software installation process. The following procedure may be used to change TCP/IP settings, if necessary.



1. Open System Preferences and select Network.

2. A window should pop up indicating that a new port has been detected. It will be named **USB-ADSL Modem.**



Click OK.

3. From the **Show** pull down menu, select the new port, **USB-ADSL Modem.**

006	Network	
Show All	Displays Sound Network Startup Disk	
Show ✔	Built–in Ethernet Internal Modem USB–ADSL Modem	•
_	Active Network Ports	ies Modem
	Configure: Using PPP	•
	IP Address: (Provided by PPP server) Subnet Mask:	Domain Name Servers (Optional)
	Router:	Search Domains (Optional)
		Example: apple.com, earthlink.net
Clie	ck the lock to prevent further changes.	Apply Now

4. Select the Modem tab. In the Modem pull down menu, select ADSL USB Modem. Uncheck Wait for dial tone

Network
Iplays Sound Network Startup Disk
Location: Automatic
-ADSL Modem 🔹
TCP/IP PPP Proxies Modem
Modem: ADSL USB Modem
Off
O Pulse
☑ Show modem status in menu bar

before dialing. Check **Show Modem Status in menu** bar.

5. Select the **PPP** tab. Enter your username (account name). If you want to make your password permanently saved, enter it and check **Save password.** Configure any other **PPP Options** as desired.

	Locati	on: Auto	matic	*	
Show: USB-A	DSL Modern		:		
	TCP/	IP PPP	Proxies	Modem	
	Service Provider				(Optional)
Tele	phone Number				
AJ	ternate Number				(Optional)
Account Name:		gspn]	
	Password				1
		Save p Checkin access	assword ng this box a this Internet	flows all users account wither	of this computer to it entering a password.

6. Select the **TCP/IP** tab and select the way you would like to obtain your IP address. The recommended way is

			Netwo	ork		
how All	Displays Sound	Network	Startup Disk			
		Location	Automati	c	\$	
Show: E	thernet Adapt	or (en4)	+]		
~	ſ	TCP/IP	PPPoE Ap	pleTalk	Proxies	
	Configure:	Using PP	P		*	
				Doma	in Name Serv	ers (Optional)
	IP Address:	193.168.((Provided b).111 y PPP server)			
S	ubnet Mask:	255.255.2	255.0			
	Router:	193.168.0	0.1	Search	n Domains	(Optional)
Etherr	net Address:	ba:be:ca:f	e:ba:be	Examp	le: apple.com, e	earthlink.net

Configure Using PPP.

7. Click **Apply Now.** Close the System Preferences application. The installation and configuration is now complete.

Establishing a Connection

- Open the Internet Connection application (which looks like a modem dialer) by clicking the screen and selecting **Open Internet Connection** from the menu.
- 2. In the **Configuration** drop down menu, select your adapter's port **USB-ADSL Modem** and fill in the password

00	USB-ADSL Modem
Configuration:	USB-ADSL Modem
Service Provider:	
Telephone Number:	1
Alternate Number:	
Name:	gspn
Password:	••••••
	Show modem status in menu bar
These settings can be	changed in Network Preferences.
-	
Status: Idle	Connect

if it was not provided in Step 5 above and click Connect.

The Internet Connection application will display the progress of the connection. Upon completion, you will be connected to the Internet. The **Disconnect** button may be used to remove the connection, effectively disconnecting from the Internet.