


DSL-2642B IPTV Configuration Guide




This document will detail how to configure the DSL-2642B for IPTV support.

Prerequisites


- Verify that you are registered to the TPG IPTV Service and that your area has IPTV support.
- Ensure VLC Player is installed on your system www.videolan.org
- Select 'Mozilla Plugin' when installing VLC Player on your PC.




1. Log in to the modem with the computer connected to the modem via Ethernet.
 - URL: <http://192.168.1.1> (default)
 - Username: admin
 - Password: admin (default)
 - Graphic Authentication: (randomly generated)



2. Select the **INTERNET SETUP** button in the left menu.




3. Select **ADD** to create a new PVC / Profile.




4. Set the following to configure the profile to support IPTV.
 - **VPI: 0**
 - **VCI: 35**
 - **EoA**
 - **Encapsulation: LLC/SNAP-BRIDGING**
 - **Service Category: UBR without PCR**
 - **Enable Quality of Service**

- Select **Bridging** for the WAN Service type:





5. Click **APPLY** to activate the changes

6. Select **ADVANCED** from the top menu once the page returns to the Internet Setup screen with the new profile added.




7. Select **Network Tools > IGMP** from the left menu.





8. Enable IGMP Snooping by selecting the checkbox.
9. Click **APPLY** to activate the change.
10. Click the **MAINTENANCE** button in the top menu



11. Select **REBOOT** to reboot the device and activate all changes made.

12. Navigate to www.tpg.com.au/iptv in your browser and log in using your TPG username and password.



13. The IPTV stream should successfully start

