

## Product Highlights

### High-Speed Internet

Latest ADSL2/2+ standards provide Internet transmission of up to 24 Mbps downstream for fast downloads and smooth streaming media

### High-Performance Wireless

Fast 802.11n wireless gives you superior speed and range while remaining compatible with older 802.11g/b devices

### Safe Connection

Robust security features keep your connection secure, preventing unauthorized access to the network while minimizing traffic for a smooth connection



## DSL-2740M

# Wireless N300 ADSL2+ Modem Router

## Features

### Superior Performance Wireless

- Integrated ADSL2/2+
- 802.11n wireless LAN
- Four Ethernet switch ports

### Robust Security Features

- WPA/WPA2 and WEP
- Stateful Packet Inspection (SPI)
- Network Address Translation (NAT)

### Smooth Connectivity

- Supports download speeds up to 24 Mbps
- Auto MDI/MDIX
- Quality of Service (QoS)

The DSL-2740M Wireless N ADSL2+ 4-Port Wi-Fi Router is a versatile, high-performance router for a home or small office. With integrated ADSL2/2+, supporting download speeds up to 24 Mbps, firewall protection, Quality of Service (QoS), 802.11n wireless LAN, and four Ethernet switch ports, the Wireless N300 ADSL2+ Modem Router provides all the functions that a user needs to establish a secure and high-speed link to the Internet.

## Reliable Wireless Connection

Featuring 802.11n, the DSL-2740M reaches wireless speeds that are up to six times faster than 802.11g. Maximize wireless performance by connecting it to computers equipped with wireless N interfaces and stay connected from virtually anywhere in the home and in the office. Featuring a 2 x 2 MIMO antenna configuration, wireless devices can take advantage of expanded wireless coverage. Supporting 802.11g and 802.11b, existing wireless devices can also connect to the network easily and quickly while enjoying significantly improved reception.

## Solid Security

The DSL-2740M's security features prevent unauthorized access to your network from both wireless intruders and Internet hackers. Stateful Packet Inspection (SPI) inspects the contents of incoming packets before they are allowed in, while hacker logging helps to protect your network against Denial of Service (DoS) attacks. Additionally, it supports Wi-Fi Protected Access (WPA/WPA2) for flexible security and data encryption while a Wi-Fi Protected Setup (WPS) button provides an easy way to establish a secure wireless connection.

## Enhanced Features

The Wireless N300 ADSL2+ Modem Router offers Quality of Service (QoS), which allows priority queues to enable a group of home or office users to experience a smooth network connection without worrying about traffic congestion. Virtual server allows users to forward ports for remote access. In addition, it includes four Ethernet ports for connecting PCs and other devices, making the DSL-2740M a logical choice for users who want a versatile and fast Wi-Fi router.

**Technical Specifications**

**General**

Device Interfaces	<ul style="list-style-type: none"> <li>• RJ-11 ADSL port</li> <li>• 4 x RJ-45 10/100BASE-TX Ethernet ports with auto MDI/MDIX</li> <li>• Factory reset button</li> </ul>	<ul style="list-style-type: none"> <li>• Built-in 802.11n wireless LAN</li> <li>• WPS button</li> <li>• Power on/off switch</li> </ul>
ADSL Standards	<ul style="list-style-type: none"> <li>• Multi-mode</li> <li>• ANSI T1.413 Issue 2</li> <li>• ITU G.992.1 (G.dmt) Annex A</li> </ul>	<ul style="list-style-type: none"> <li>• ITU G.992.2 (G.lite) Annex A</li> <li>• ITU G.994.1 (G.hs)</li> </ul>
ADSL2 Standards	<ul style="list-style-type: none"> <li>• ITU G.992.3 (G.dmt.bis)</li> <li>• Annex A/L/M, ITU G.992.4 (G.lite.bis) Annex A</li> </ul>	<ul style="list-style-type: none"> <li>• ITU G.992.5 Annex L/M (optional)</li> </ul>

**Functionality**

Wireless Features	<ul style="list-style-type: none"> <li>• 802.11n/g/b standards</li> <li>• Wireless speed: up to 54 Mbps (802.11g), 300 Mbps (802.11n)</li> </ul>	<ul style="list-style-type: none"> <li>• Frequency range: 2.4 GHz to 2.484 GHz</li> <li>• Antennas: Dual 2x2 MIMO antennas</li> </ul>
DSL Features	<ul style="list-style-type: none"> <li>• G.dmt: 8 Mbps downstream, 832 Kbps upstream</li> <li>• G.lite: 1.5 Mbps downstream, 512 Kbps upstream</li> <li>• ADSL2: 12 Mbps downstream, 1 Mbps upstream</li> <li>• ATM Forum UNI3.1/4.0 PVC (up to 8 PVCs)</li> <li>• ADSL2+: 24 Mbps downstream, 1 Mbps upstream</li> <li>• VC and LLC based multiplexing</li> </ul>	<ul style="list-style-type: none"> <li>• PPP over Ethernet (PPPoE)</li> <li>• PPP over ATM (RFC 2364)</li> <li>• ITU-T I.610 OAM F4/F5</li> <li>• ATM Adaptation Layer Type 5 (AAL5)</li> <li>• ATM QoS (Traffic Shaping)</li> <li>• Bridged or routed Ethernet encapsulation</li> </ul>
Router Features	<ul style="list-style-type: none"> <li>• NAT &amp; NATP</li> <li>• DHCP server/client/relay</li> <li>• Static Routing, RIP v.1, v.2</li> <li>• Universal Plug and Play (UPnP) compliant</li> <li>• Dynamic Domain Name System (DDNS)</li> <li>• Virtual server</li> </ul>	<ul style="list-style-type: none"> <li>• SNTP, DNS proxy and IGMP proxy</li> <li>• Built-in NAT firewall</li> <li>• Stateful Packet Inspection (SPI)</li> <li>• DoS attacks prevention</li> <li>• Packet filtering (IP/ICMP/TCP/UDP)</li> <li>• Supports IPv6</li> </ul>
Virtual Private Network (VPN)	<ul style="list-style-type: none"> <li>• Multiple PPTP/IPSec/L2TP pass-through</li> </ul>	
Device Configuration/Management	<ul style="list-style-type: none"> <li>• Installation wizard</li> <li>• Web-based GUI for configuration, firmware upgrade</li> </ul>	<ul style="list-style-type: none"> <li>• Telnet</li> <li>• Syslog monitoring</li> </ul>
Quality of Service	<ul style="list-style-type: none"> <li>• 802.1p (0 to 7) traffic tagging</li> <li>• IGMP snooping with 32 Multicast groups</li> </ul>	<ul style="list-style-type: none"> <li>• PVC/VLAN port mapping (bridge mode)</li> </ul>
Security	<ul style="list-style-type: none"> <li>• IGMP</li> <li>• PVC/VLAN port mapping (bridge mode) 64/128 bits</li> <li>• WEP data encryption</li> </ul>	<ul style="list-style-type: none"> <li>• WPA/WPA2 (Wi-Fi Protected Access) security</li> <li>• MAC address-based access control</li> <li>• WPS</li> </ul>
Status LEDs	<ul style="list-style-type: none"> <li>• Power</li> <li>• LAN (1 to 4)</li> <li>• WLAN</li> </ul>	<ul style="list-style-type: none"> <li>• WPS</li> <li>• DSL</li> <li>• Internet</li> </ul>

**Physical**

Dimensions	<ul style="list-style-type: none"> <li>• 160 x 120 x 25 mm (6.30 x 4.72 x 0.98 inches)</li> </ul>	
Weight	<ul style="list-style-type: none"> <li>• 205 grams (7.2 ounces)</li> </ul>	
Power	<ul style="list-style-type: none"> <li>• Input: 100 to 240 V AC, 50/60 Hz</li> </ul>	<ul style="list-style-type: none"> <li>• Output: 12 V DC 0.5 A (via external adapter)</li> </ul>
Temperature	<ul style="list-style-type: none"> <li>• Operating: 0 to 40 °C (32 to 104 °F)</li> </ul>	<ul style="list-style-type: none"> <li>• Storage: -20 to 65 °C (-4 to 149 °F)</li> </ul>
Humidity	<ul style="list-style-type: none"> <li>• Operating: 0% to 90% non-condensing</li> </ul>	<ul style="list-style-type: none"> <li>• Storage: 5% to 95% non-condensing</li> </ul>
Certifications	<ul style="list-style-type: none"> <li>• CE</li> </ul>	<ul style="list-style-type: none"> <li>• Anatel</li> </ul>

# DSL-2740M Wireless N300 ADSL2+ Modem Router

Order Information	
Part Number	Description
DSL-2740M	Wireless N300 ADSL2+ Modem Router

<sup>1</sup> Maximum wireless signal rate derived from IEEE standard 802.11ac specifications which are subject to change. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead, lower actual data throughput rate. Environmental factors will adversely affect wireless signal range.

Updated 2016/11/29