D-Link ADSL Router - Internet Explorer

http://192.168.1.1/login.cgi

File Edit View Favorites Tools Help SnagIt

D-Link ADSL Router

Page Tools

Product Page: DVA-G3670B | Site Map | Firmware Version: AUS_1.27

D-Link

DVA-G3670B

SETUP | ADVANCED | VOICE | MAINTENANCE | STATUS | HELP

- Advanced Wireless
- Port Forwarding
- Port Triggering
- DMZ
- Parental Control
- Filtering Options
- Firewall Settings
- DNS
- Dynamic DNS
- Network Tools
- Routing
- Schedules
- TR-069 Client
- Print Server
- Logout

BRIDGE FILTERING

Bridge Filtering is only effective on ATM PVCs configured in Bridge mode. **ALLOW** means that all MAC layer frames will be **ALLOWED** except those matching with any of the specified rules in the following table. **DENY** means that all MAC layer frames will be **DENIED** except those matching with any of the specified rules in the following table.

Create a filter to identify the MAC layer frames by specifying at least one condition below. If multiple conditions are specified, all of them take effect. Click "Apply" to save and activate the filter.

Bridge Filtering Global Policy:

- (●) **ALLOW** all packets but **DENY** those matching any of specific rules listed
- ( ) **DENY** all packets but **ALLOW** those matching any of specific rules listed

Apply Cancel

BRIDGE FILTER SETUP

	VPI/VCI	Protocol	Destination MAC	Source MAC	Frame Direction	Schedule Rule

Add Edit Delete

Helpful Hints...

Note : You must first create a **Bridged** connection to use **Bridge Filter**.

You can create a **Bridged** connection by going to **Setup -> Internet Setup**.

More...

Done Internet 100%