

## **CAT6 UTP KEYSTONE JACKS**

## **Cat6 Keystone Jacks**

D-Link Category 6 keystone jacks are RJ45 8P 8C 50u jacks suitable for 22-26 AWG stranded and solid wire, compatible with both 110 & Krone punch down tool. They are available in universal labels color coded for T568A and T568B wiring schemes and fit in high density keystone patch panel. It supports IEC 60603-7-4 and complied with ANSI/TIA/EIA-568-C.2 standard.





## **SPECIFICATIONS**

RJ45 Jack:	Housing: ABS+PC, UL 94V-0, with optional color
Contact Bracket:	PC, UL 94V-2, transparent color
RJ45 Jack Contact:	Material-phosphor bronze with nickel plated
	Finish: 50 micro-inch gold plated on plug
	contact area
IDC:	Housing- PC + glass fiber, UL 94V-2
	Terminal: Phosphor bronze with tin
	plated
IDC CAP:	ABS, UL 94V-0
Insertion Cycles:	750 times
Operating Temperature:	–10°C to 60°C
Storage Temperature:	–10°C to 80°C
Current Rating:	1.5A
Insulation Resistance:	>100 Megaohms
Contact Resistance	
Variations:	20 Milliohms
Insertion Force:	20N (Max)

## **ORDERING INFORMATION**

CAT 5E Keystone Jacks		
Part Code	Description	Color Code
NKJ-C6WHI1B21	Cat6 UTP Keystone Jack	White
NKJ-C6BLU1B21	Cat6 UTP Keystone Jack	Blue
NKJ-C6RED1B21	Cat6 UTP Keystone Jack	Red
NKJ-C6GRN1B21	Cat6 UTP Keystone Jack	Green
NKJ-C6YEL1B21	Cat6 UTP Keystone Jack	Yellow



D-Link Corporation No. 289 Xinhu 3rd road, Neihu, taipei 114, taiwan Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks belong to their respective owners. ©2010 D-Link Corporation. All rights reserved. Release 01 (May 2010)