

### Cat 6 UTP Loaded Patch Panel

D-Link Category 6 patch panels are six port RJ45 modules applied and suitable for 22-26AWG stranded and solid wire, compatible with both 110 & Krone punch down tools. D-Link patch panels have improved Cable Management with optional Cable Management bar terminating 4 pairs UTP cable. They are complied with the ANSI/TIA/EIA-568-C.2 standard.



### SPECIFICATIONS

Identification:	ID plate: <b>PVC, transparent color with paper</b>
Panel:	<b>SPCC, 1.5mm thickness with black color painted</b>
RJ45 Jack:	Housing: <b>ABS, UL 94V-0</b> Contact Brackets: <b>PC, UL 94V-2, transparent color</b>
RJ45 Jack contact:	<b>Material-phosphor bronze with nickel plated</b> Finish: <b>50 micro-inches Gold plated on plug contact area</b>
IDC:	Housing – <b>PC + glass fiber, UL 94V-2</b> Terminal: <b>Phosphor bronze with tin plated</b>
Jack Bracket Set:	<b>ABS, UL 94V-0</b>
Support Bar:	<b>SPCC, 1.5 mm thickness with black color painted</b>

### ORDERING INFORMATION

CAT6 Jack Panel	
Part Code	Description
NPP-C61BLK241	Cat6 UTP 24 Port Loaded Patch Panel
NPP-C61BLK481	Cat6 UTP 48 Port Loaded Patch Panel



D-Link Corporation  
No. 289 Xinhua 3rd road, Neihu, taipei 114, taiwan  
Specifications are subject to change without notice.  
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.  
All other trademarks belong to their respective owners.  
©2010 D-Link Corporation. All rights reserved. Release 01 (May 2010)