

Cat 6 UTP Loaded Patch Panel

D-Link Category 6 patch panels are six port RJ45 modules applied and suitable for 22-26AWG stranded and solid wire, compatible with both 110 & Krone punch down tools. D-Link patch panels have improved Cable Management with optional Cable Management bar terminating 4 pairs UTP cable. They are complied with the ANSI/TIA/EIA-568-C.2 standard.



SPECIFICATIONS

Identification:	ID plate: PVC, transparent color with paper
Panel:	SPCC, 1.5mm thickness with black color painted
RJ45 Jack:	Housing: ABS, UL 94V-0 Contact Brackets: PC, UL 94V-2, transparent color
RJ45 Jack contact:	Material-phosphor bronze with nickel plated Finish: 50 micro-inches Gold plated on plug contact area
IDC:	Housing – PC + glass fiber, UL 94V-2 Terminal: Phosphor bronze with tin plated
Jack Bracket Set:	ABS, UL 94V-0
Support Bar:	SPCC, 1.5 mm thickness with black color painted

ORDERING INFORMATION

CAT6 Jack Panel	
Part Code	Description
NPP-C61BLK241	Cat6 UTP 24 Port Loaded Patch Panel
NPP-C61BLK481	Cat6 UTP 48 Port Loaded Patch Panel



D-Link Corporation
No. 289 Xinhua 3rd road, Neihu, taipei 114, taiwan
Specifications are subject to change without notice.
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners.
©2010 D-Link Corporation. All rights reserved. Release 01 (May 2010)