

Vigilance 4 Megapixel H.265 Outdoor Dome Camera

High-definition professional surveillance and security solution, suitable for small, medium, and large enterprises.

DCS-4614EK

- 1/2.8" 4 Megapixel progressive CMOS sensor
- Resolution of up to 2592 × 1520 at 30 fps
- H.265, H.264 and MJPEG codec support
- Wide Dynamic Range (WDR) image enhancement
- Supports 2D/3D noise reduction
- Motion detection, corridor mode, and privacy mask
- Fixed 2.8 mm lens with an F2.0 aperture
- Build-in IR LED illuminator with a 30 m range
- 10/100 Base-TX Fast Ethernet port with PoE (Power over Ethernet) ensures easy integration into your network
- IP66 compliant housing allows for installation in a wide range of climates, from -30 °C to 50 °C
- microSD card slot for local recording
- ONVIF Profile S compliant
- Equipped with night vision technology from Sony for increased light sensitivity
- Vandal-proof IK10-rated housing
- Supports D-Link's free D-ViewCam™ suite of management software



IP66 Compliant

Water-resistant and dust-tight housing with an operating temperature range of -30 to 50 °C



Night Vision

Optimized for increased image quality in low-light environments



30 Meter Illumination

See up to 30 meters in the dark with a built-in IR-cut filter and IR LED



Wide Dynamic Range

Improved image quality in high-contrast conditions with WDR



PoE Capable

Supports 802.3af PoE for flexible and simple installation



microSD Card¹

Equipped with a microSD card slot for local storage

Camera

Camera Hardware Profile	1/2.8" 4-megapixel progressive CMOS sensor 30 meter IR illumination distance Minimum illumination: Color: 0.05 lux @(F2.0, AGC ON) B/W: 0 lux @(IR LED ON) Built-in Infrared-Cut Removable (ICR) Filter module 18x digital zoom Minimum object distance 0.5 m Focal length: 2.8 mm Aperture: F2.0 Angle of view: (H) 100° (V) 58° (D) 126° 3-axis adjustment angle (non-motorized): Pan: 15° - 90° Tilt: 350° Rotate: 335°
-------------------------	---

Camera Housing	IP66 certified weatherproof housing Supports IK10 standard
----------------	---

Image Features	Configurable image size/quality/frame rate/bit rate Time stamp and text overlays Configurable shutter speed/brightness/saturation/contrast/sharpness/3D filter Configurable motion detection area Configurable privacy mask zones Auto White Balance (AWB) Auto Gain Control (AGC) Wide Dynamic Range (WDR) Corridor mode
----------------	---

Video Compression	Simultaneous H.265/H.264/MJPEG format compression JPEG for still images
-------------------	--

Max. Video Resolution and Frame Rate	2592 x 1520 at up to 30 fps
--------------------------------------	-----------------------------

External Device Interfaces	microSD card slot ¹ Reset button 10/100 Base-TX Fast Ethernet port (supports 802.3af PoE Class 3)
----------------------------	--


Network

Network Protocols	IPv4 HTTP/HTTPS RTSP/RTP/RTCP TCP UDP DHCP DNS DDNS NTP FTP SMTP Client ONVIF Profile S compliant ARP ICMP PPPoE SNMP v1/v2c/v3
-------------------	--



System Management

Event Management	<ul style="list-style-type: none"> Motion detection Multiple event notifications Event notification and uploading of snapshots via e-mail or FTP Video recording via microSD card, D-ViewCam, D-Link NVR or ONVIF-compliant NAS
Remote Management	<ul style="list-style-type: none"> Remote management via D-ViewCam software Remotely take snapshots/video clips and save to a local hard drive Configuration interface accessible via a web browser
System Requirements for Web Interface	<ul style="list-style-type: none"> Operating System: Microsoft Windows Browser: Internet Explorer 11 for full function; Chrome and Firefox (MJPEG only)
D-ViewCam System Requirements	<ul style="list-style-type: none"> Operating System: Windows 10 Protocol: Standard TCP/IP
D-ViewCam Software Functions	<ul style="list-style-type: none"> Supports all management functions provided in the web interface Scheduled motion trigger or manual recording options Remote management of up to 64 cameras Viewing of up to 64 cameras on one screen



General

Weight	470 g ± 5%
External Power Adapter	100 to 240 V AC, 50/60 Hz (Input), 12 V DC 1.5 A (Output)
Power Consumption	8 W ± 5% (PoE)
Operating Temperature	-30 to 50 °C (-22 to 122 °F)
Storage Temperature	-20 to 70 °C (-4 to 158 °F)
Operating/Storage Humidity	Max. 90% non-condensing
Dimension	∅ 110 mm x 85.4 mm (∅ 4.3 in x 3.4 in)
Certifications	CE, FCC, RCM

Order Information

DCS-4614EK	Vigilance 4 Megapixel H.265 Outdoor Dome Camera
Hardware Version	A

¹ microSD card not included. Supports capacity up to 256 GB.

Mounts			
Model Name	Pole-Mount Bracket	Wall-Mount Bracket	Junction Box
Model Number	DCS-37-4	DCS-37-5	DCS-37-6
Product Image			
Dimensions (L x W x H)	L121 x W52 x H120 mm	L183 x ø120 x H84 mm	ø121 x H46 mm
Weight	470 g	350 g	420 g
Maximum Load	3 kg	3 kg	3 kg
Material	Metal	Metal	Metal

Note: The DCS-37-4 must be used in conjunction with the DCS-37-5 or the DCS-37-6 to properly mount the DCS-4614EK camera.

