



GBIC Transceivers

D-Link Gigabit Interface Converters (GBIC) are transceivers that connect Gigabit switches and 10/100Mbps switches with GBIC slots to Gigabit Ethernet networks, providing high-speed connections over the fiber-optic or twisted-pair cable. The fiber-optic transceivers have standard SC connectors for connection compatibility. Support Auto Negotiation.

Hot Swappable

All D-Link GBIC transceivers are hot-swappable. You can remove or replace the GBIC transceiver with the system powered on. This permits modules and GBICs to be added or swapped without interrupting the network.

Full Size GBIC

All transceivers described in this datasheet have full GBIC size. (D-Link Mini GBIC transceivers are described in a separate brochure). These transceivers slide into a full-size GBIC slot. They provide the necessary signal amplification

for data to be transmitted to the network cable from the port, and vice versa, for the port to receive data from the network cable.

Applications

Applications of the fiber transceivers include distributed multi-processing, Gigabit switch cascading, high-speed I/O file transfer, bus extension application, and channel extender/data storage.

Multi-mode Fiber Transceiver (550 m)

DGS-701

- SC 1000BASE-SX port (IEEE 802.3z standard)
- Full duplex operation
- 802.3x flow control support
- Fiber type: 50um/125um 500MHz-km multi-mode fiber up to 550 m
- Wave length: 850 m
- Power support: 3.3V

Single-mode Fiber Transceiver (5 km)

DGS-702

- SC 1000BASE-LX port (IEEE 802.3z standard)
- Full duplex operation
- 802.3x flow control support
- Fiber type: 9um single-mode fiber up to 5 km
- Wave length: 1310 m
- Power support: 3.3V

GBIC Transceiver

Technical Specifications

Transceiver

Single-mode Fiber Transceiver (10 km)

DGS-703

- SC 1000BASE-LX port (IEEE 802.3z standard)
- Full duplex operation
- 802.3x flow control support
- Fiber type: 9um single-mode fiber up to 10 km
- Wave length: 1310 m
- Power support: 3.3V and 5V
- Power budget: 10.5dB

Single-mode Fiber Transceiver (30 km)

DGS-704

- SC 1000BASE-LX port (IEEE 802.3z standard)
- Full duplex operation
- 802.3x flow control support
- Fiber type: 9um single-mode fiber up to 30 km
- Wave length: 1310 m
- Power support: 3.3V and 5V
- Power budget: 18dB

Multi-mode Fiber Transceiver (550 m)

DGS-707

- SC 1000BASE-SX port (IEEE 802.3z standard)
- Full duplex operation
- 802.3x flow control support
- Fiber type: 50um or 62.5 multi-mode fiber up to 550 m
- Wave length: 850 m
- Power support: 3.3V and 5V
- Power budget: 7.5dB

Single-mode Fiber Transceiver (70 km)

DGS-708

- SC 1000BASE-LX port (IEEE 802.3z standard)
- Full duplex operation
- 802.3x flow control support
- Fiber type: 9um single-mode fiber up to 70 km
- Wave length: 1550 m
- Power support: 3.3V and 5V
- Power budget: 23dB

Copper Twisted-pair Transceiver (100 m)

DGS-711

- RJ-45 100BASE-TX/1000BASE-T port (IEEE 802.3u/802.3ab standards)
- Full duplex for Gigabit
- 802.3x flow control support
- Cable type: Cat. 5 twisted-pair up to 100 m
- Power support: 3.3V and 5V

Multi-mode Fiber Transceiver (2 km)

DEM-310GM2

- 1000BASE-SX port (IEEE 802.3z standard)
- Full duplex operation
- 802.3x flow control support
- Fiber type: 62.5um multi-mode fiber up to 2 km
- Wave length: 1310nm
- Power support: 3.3V/5V

Ordering Information

GBIC Transceiver

DGS-701	For 1000BASE-SX, multi-mode fiber, 550 m max.
DGS-702	For 1000BASE-LX, single-mode fiber, 5 km max.
DGS-703	For 1000BASE-LX, single-mode fiber, 10 km max.
DGS-704	For 1000BASE-LX, single-mode fiber, 30 km max.
DGS-707	For 1000BASE-SX, multi-mode fiber, 550 m max.
DGS-708	For 1000BASE-LX, single-mode fiber, 70 km max.
DEM-310GM2	For 1000 BASE-SX, multi-mode fiber, 2km max.
DGS-711	For 1000BASE-T, Cat. 5 cable, 100 m max.

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A	TEL: 1-949-788-0805	FAX: 1-949-753-7033
Canada	TEL: 1-905-8295033	FAX: 1-905-8295095
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Benelux	TEL: 31-10-2045740	FAX: 31-10-2045880
Italy	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Norway	TEL: 47-22-309075	FAX: 47-22-309085
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Finland	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
China	TEL: 86-10-8518-2533	FAX: 86-10-8518-2250
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914
Middle East	TEL: 9714-8834234	FAX: 9714-8834394
Turkey	TEL: 90-212-335-2553	FAX: 90-212-335-2500
Chile	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brasil	TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
South Africa	TEL: 27(0)1266-52165	FAX: 27(0)1266-52186
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE
Rev. 03 (Apr. 2003)
Printed in Taiwan