

D-Link NVR supported cameras

(FW version: V1.10)

| NVR Model | Supported camera brands (for specific models see tables below) |
|-----------|---|
| DNS-722-4 | D-Link |
| DNS-726-4 | D-Link, ACTi, Arecont Vision, Axis, Cisco, IQinVision, Mobotix, Panasonic, Sony |

Remark: DNS-722-4 doesn't support DI/DO function.

| D-Link | | | | | | | | | | | |
|--|---------------------------------|----------------|--------------------------|----------------|----------------|---------|--------------|-------------|------------------|------|---------------------|
|  | | | | | | | | | | | |
| Device Name | Tested Firmware | Hardware Ver. | Video Format | Video Channels | Max Resolution | Audio | I/O Channels | PTZ Support | Motion Detection | UPnP | Remarks |
| DCS-1100 | 1.00 | A1 A2 | MPEG4 M-JPEG | 1 | 640x480 | One-way | 0/0 | No | Yes | Yes | Supported by design |
| DCS-1130 | 1.00 | A1 A2 | MPEG4 M-JPEG | 1 | 640x480 | One-way | 0/0 | No | Yes | Yes | Supported by design |
| DCS-2100 | | A1 | H.263 | 1 | 720x576 | One-way | 0/0 | No | Yes | Yes | Supported by design |
| DCS-2100G | | A1 | H.263 | 1 | 720x576 | One-way | 0/0 | No | Yes | Yes | Supported by design |
| DCS-2102 | | A1 A2 | MPEG4 M-JPEG | 1 | 1280x1024 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| DCS-2120 (TW) | 0201tw | B1 | MPEG4 | 1 | 720x576 | One-way | 1/1 | No | Yes | Yes | |
| DCS-2120 | | A2 | MPEG4 | 1 | 720x576 | One-way | 0/0 | No | Yes | Yes | Supported by design |
| DCS-2121 | | A1 A2 | MPEG4 M-JPEG | 1 | 1280x1024 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| DCS-3110 | | A1 A2 | MPEG4 M-JPEG | 1 | 1280x1024 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| DCS-3220 | | A2 | MPEG4 | 1 | 720x576 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| DCS-3220G | | B2 | MPEG4 | 1 | 720x576 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| DCS-3410 | | A1 A2 | MPEG4 M-JPEG | 1 | 704x576 | One-way | 2/1 | No | Yes | Yes | Supported by design |
| DCS-3411 | | A1 A2 A3 | MPEG4 M-JPEG H.264 | 1 | 640x480 | One-way | 2/1 | Yes | Yes | Yes | Supported by design |
| Note: | PTZ Support: pan and tilt only. | | | | | | | | | | |
| DCS-3415 | 1.00 | A1 A2 A3 | MPEG4 M-JPEG | 1 | 640x480 | One-way | 1/1 | No | Yes | Yes | |
| Note: | PTZ Support: zoom only. | | | | | | | | | | |
| DCS-3420 | | A2 | MPEG4 M-JPEG | 1 | 720x576 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| DCS-3430 | 1.01 | A1 A2 A3 | MPEG4 M-JPEG H.264 | 1 | 640x480 | One-way | 2/1 | No | Yes | Yes | |
| DCS-3710 | 0.24.06 | A1 | MPEG4 M-JPEG | 1 | 1280x960 | One-way | 2/1 | Yes | Yes | Yes | |
| DCS-5220 (TW) | | A2 | MPEG4 | 1 | 640x480 | One-way | 0/0 | Yes | Yes | Yes | Supported by design |
| DCS-5220 | 0200 | B1 | MPEG4 MJPEG | 1 | 640x480 | One-way | 0/0 | Yes | Yes | Yes | |
| DCS-5230 | 1.00 | A1 | MPEG4 M-JPEG | 1 | 1280x1024 | One-way | 1/1 | Yes | Yes | Yes | |
| DCS-5300 | 1.05 | A3 A4 | MPEG4 | 1 | 704x576 | One-way | 1/1 | Yes | Yes | Yes | |
| DCS-5300G | | B2 | H.263 | 1 | 720x576 | One-way | 1/1 | Yes | Yes | Yes | Supported by design |
| DCS-5610 | | A1 A2 | MPEG4 M-JPEG | 1 | 720x576 | One-way | 1/1 | Yes | Yes | Yes | Supported by design |
| DCS-5605 | | A1 | H.264 MPEG4 M-JPEG | 1 | 720x576 | One-way | 1/1 | Yes | Yes | Yes | |
| DCS-5635 | | A1 | H.264 MPEG4 M-JPEG | 1 | 720x576 | One-way | 1/1 | Yes | Yes | Yes | |
| DCS-6110 | 1.00 | A1 | M-JPEG | 1 | 720x576 | No | 1/1 | No | Yes | Yes | |

| | | | | | | | | | | | |
|-----------|---------------------------------|----------|-----------------|---|---------|---------|-----|-----|-----|-----|------------------------|
| | | A2 A3 | | | | | | | | | |
| DCS-6111 | 1.00 | A1 A2 | MPEG4 M-JPEG | 1 | 640x480 | One-way | 1/1 | No | Yes | Yes | |
| DCS-6410 | 1.00 | A1 A2 | MPEG4 M-JPEG | 1 | 704x576 | One-way | 2/1 | No | Yes | Yes | Supported by design |
| DCS-6620 | 1.05 | A3 | MPEG4 M-JPEG | 1 | 704x576 | One-way | 0/0 | Yes | Yes | Yes | |
| DCS-6620G | 1.05 | A4 | MPEG4 M-JPEG | 1 | 720x576 | One-way | 0/0 | Yes | Yes | Yes | |
| DCS-7410 | 1.00 | A1 A2 | MPEG4 M-JPEG | 1 | 704x576 | One-way | 2/1 | Yes | Yes | Yes | |
| DCS-7510 | 1.00 | A1 A2 | MPEG4 M-JPEG | 1 | 704x576 | One-way | 2/1 | Yes | Yes | Yes | |
| Note: | PTZ Support: pan and tilt only. | | | | | | | | | | |
| DCS-900 | 1.00 | B1 B2 | MPEG4 | 1 | 640x480 | One-way | 0/0 | No | No | Yes | Supported by design |
| DCS-910 | 1.00 | A1 A2 | MPEG4 | 1 | 640x480 | One-way | 0/0 | No | No | Yes | Supported by design |
| DCS-920 | | A1 A2 | M-JPEG | 1 | 640x480 | No | 0/0 | No | No | Yes | Supported by design |
| DCS-950 | | A3 | MPEG4 | 1 | 640x480 | One-way | 0/0 | No | No | Yes | Supported by design |
| DCS-950G | | A4 | MPEG4 | 1 | 640x480 | One-way | 0/0 | No | No | Yes | Supported by design |
| DCS-G900 | | A1 A2 | M-JPEG | 1 | 640x480 | No | 0/0 | No | No | Yes | Supported by design |
| DVS-104 | | A1 | M-JPEG | 4 | 720x576 | No | 4/2 | No | Yes | Yes | Supported by design |
| DVS-301 | | A2 | H.263 | 1 | 704x576 | One-way | 1/1 | No | Yes | Yes | Supported by design |

ACTi



| Device Name | Tested Firm-ware | Video Format | Video Channels | Max Resolution | Audio | I/O Channels | PTZ Support | Motion Detect-ion | UPnP | Remarks |
|-------------|-------------------------|-----------------|----------------|----------------|---------|--------------|-------------|-------------------|------|------------------------|
| ACD2100 | A1D-220-V3.0 8.08-AC | MPEG4 M-JPEG | 1 | 720x480 | One-way | 2/2 | Yes | Yes | No | |
| ACD2200 | | MPEG4 M-JPEG | 4 | 720x480 | One-way | 8/8 | Yes | Yes | No | Supported by design |
| ACD2300 | | MPEG4 M-JPEG | 8 | 720x480 | One-way | 16/16 | Yes | Yes | No | Supported by design |
| ACD2400 | AGD-R2N-V2.0 5.02-AC | MPEG4 M-JPEG | 16 | 720x480 | One-way | 2/2 | Yes | Yes | No | |
| ACM1231 | | MPEG4 M-JPEG | 1 | 1280x1024 | One-way | 0/0 | No | Yes | No | Supported by design |
| ACM1232 | | MPEG4 M-JPEG | 1 | 1280x1024 | One-way | 0/0 | No | Yes | No | Supported by design |
| ACM1311 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 0/0 | No | Yes | No | Supported by design |
| ACM1431 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 0/0 | No | Yes | No | Supported by design |
| ACM1432 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 0/0 | No | Yes | No | Supported by design |
| ACM3001 | | MPEG4 M-JPEG | 1 | 640x480 | One-way | 0/0 | No | Yes | No | Supported by design |
| ACM3211 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 0/0 | Yes | Yes | No | Supported by design |
| ACM3311 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 0/0 | Yes | Yes | No | Supported by design |
| ACM3401 | | MPEG4 M-JPEG | 1 | 1280x1024 | One-way | 0/0 | No | Yes | No | Supported by design |
| ACM3411 | | MPEG4 M-JPEG | 1 | 1280x1024 | One-way | 0/0 | No | Yes | No | Supported by design |
| ACM4100 | A1D-220-V3.0 9.14-AC | MPEG4 M-JPEG | 1 | 640x480 | One-way | 0/0 | No | Yes | No | Supported by design |
| ACM4200 | | MPEG4 M-JPEG | 1 | 1280x1024 | One-way | 0/0 | No | Yes | No | Supported by design |
| ACM5001 | | MPEG4 M-JPEG | 1 | 640x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| ACM5601 | A1D-220-V3.0 8.08-AC | MPEG4 M-JEPG | 1 | 1280x1024 | One-way | 1/1 | No | Yes | No | |
| ACM5611 | | MPEG4 M-JPEG | 1 | 1280x1024 | One-way | 1/1 | No | Yes | No | Supported by design |

| | | | | | | | | | | |
|----------|---|-----------------|---|-----------|---------|-------|-----|-----|----|------------------------|
| ACM5711 | A1D-220-V3.0 8.08-AC | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | |
| ACM7411 | | MPEG4 M-JPEG | 1 | 1280x1024 | One-way | 1/1 | No | Yes | No | |
| Note: | A1D-220-V3.09.14-AC: There is problem at 160x112 resolution. | | | | | | | | | |
| CAM5200 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| CAM5201 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| CAM5221 | A1D-M2N-V2.0 8.11-AC | M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | |
| CAM5300 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| CAM5301 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| CAM5321 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| CAM5500 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| CAM6200 | A1D-2.07.14-A C | MPEG4 M-JPEG | 1 | 720x480 | One-way | 2/2 | Yes | Yes | No | Supported by design |
| CAM6220 | A1D-2.07.14-A C | MPEG4 M-JPEG | 1 | 720x480 | One-way | 2/2 | Yes | Yes | No | Supported by design |
| CAM6500 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 2/2 | Yes | Yes | No | Supported by design |
| CAM6510 | A1D-M2N-V2.0 8.11-AC | M-JPEG | 1 | 720x480 | One-way | 2/2 | Yes | Yes | No | |
| CAM6520 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 2/2 | Yes | Yes | No | Supported by design |
| CAM6600 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 2/2 | Yes | Yes | No | Supported by design |
| CAM6610 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 2/2 | Yes | Yes | No | Supported by design |
| CAM6620 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 2/2 | Yes | Yes | No | Supported by design |
| CAM6630 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 2/2 | Yes | Yes | No | Supported by design |
| CAM7100 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| CAM7120 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| CAM7200 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| CAM7220 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| CAM7300 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| CAM7301 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| CAM7320 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| CAM7321 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| CAM7322 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| SED2120 | A1D-M2N-V2.0 8.11-AC | MPEG4 | 1 | 720x480 | One-way | 0/0 | No | Yes | No | |
| SED2140 | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 2/2 | Yes | Yes | No | Supported by design |
| SED2310Q | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 2/2 | Yes | Yes | No | Supported by design |
| SED2320Q | | MPEG4 M-JPEG | 1 | 720x480 | One-way | 2/2 | Yes | Yes | No | Supported by design |
| SED2400 | | MPEG4 M-JPEG | 2 | 720x480 | One-way | 2/2 | Yes | Yes | No | Supported by design |
| SED2420 | A1D-220-V3.0 8.08-AC | MPEG4 M-JEPG | 2 | 720x480 | One-way | 0/0 | No | Yes | No | |
| SED2600 | | MPEG4 M-JPEG | 8 | 720x480 | One-way | 16/16 | Yes | Yes | No | Supported by design |
| SED2610 | | MPEG4 M-JPEG | 8 | 720x480 | One-way | 16/16 | Yes | Yes | No | Supported by design |
| SED26X0 | | MPEG4 M-JPEG | 8 | 720x480 | One-way | 16/16 | Yes | Yes | No | Supported by design |
| Note: | ACD / ACM series cameras do not support FW 3.11.11. | | | | | | | | | |
| Note: | Only two I/O are shown on the interface as adding one channel on devices with I/O function. | | | | | | | | | |

| Device Name | Tested Firmware | Video Format | Video Channels | Max Resolution | Audio | I/O Channels | PTZ Support | Motion Detect-ion | UPnP | Remarks |
|-------------|-----------------|--------------|----------------|----------------|-------|--------------|-------------|-------------------|------|---------------------|
| AV1300 | 64328 | M-JPEG | 1 | 1280x1024 | No | 0/0 | No | Yes | No | Supported by design |
| AV1305 | 64331 | M-JPEG | 1 | 1280x1024 | No | 0/0 | No | Yes | No | |
| AV2000 | 64328 | M-JPEG | 1 | 1600x1184 | No | 0/0 | No | Yes | No | Supported by design |
| AV2100 | 64328 | M-JPEG | 1 | 1600x1184 | No | 0/0 | No | Yes | No | Supported by design |
| AV2105 | 64331 | M-JPEG | 1 | 1600x1184 | No | 0/0 | No | Yes | No | |
| AV2155 | 64803 | M-JPEG | 1 | 1600x1184 | No | 0/0 | No | Yes | No | |
| AV3100 | 64328 | M-JPEG | 1 | 2048x1536 | No | 0/0 | No | Yes | No | Supported by design |
| AV3105 | 64331 | M-JPEG | 1 | 1920x1216 | No | 0/0 | No | Yes | No | |
| AV3130 | 61906 | M-JPEG | 1 | 2048x1536 | No | 0/0 | No | Need to retest | No | Supported by design |
| AV5100 | 61906 | M-JPEG | 1 | 2560x1600 | No | 0/0 | No | Yes | No | |
| AV5105 | 64331 | M-JPEG | 1 | 2560x1600 | No | 0/0 | No | Yes | No | |
| AV8180 | 65010 | M-JPEG | 4 | 1600x1184 | No | 0/0 | No | Yes | No | Supported by design |
| AV8185 | 64803 | M-JPEG | 4 | 1600x1200 | No | 0/0 | No | Yes | No | |
| AV8360 | 65010 | M-JPEG | 4 | 1600x1184 | No | 0/0 | No | Yes | No | Supported by design |

Axis



| Device Name | Tested Firmware | Video Format | Video Channels | Max Resolution | Audio | I/O Channels | PTZ Support | Motion Detect-ion | UPnP | Remark |
|-------------|-----------------|-----------------------------|----------------|----------------|---------|--------------|-------------|-------------------|------|---------------------|
| 205 | | M-JEPG | 1 | 640x480 | No | 0/0 | No | Yes | No | Supported by design |
| 206 | | M-JEPG | 1 | 640x480 | No | 0/0 | No | Yes | Yes | Supported by design |
| 206M | | M-JEPG | 1 | 1280x1024 | No | 0/0 | No | Yes | Yes | Supported by design |
| 206W | | M-JEPG | 1 | 640x480 | No | 0/0 | No | Yes | Yes | Supported by design |
| 207 | 4.40 | MPEG4 M-JEPG | 1 | 640x480 | One-way | 1/1 | No | Yes | Yes | |
| Note: | | Not support audio in M-JPEG | | | | | | | | |
| 207MW | | MPEG4 M-JEPG | 1 | 1280x1024 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| 207W | | MPEG4 M-JEPG | 1 | 640x480 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| 209FD | | MPEG4 M-JEPG | 1 | 640x480 | No | 0/0 | No | Yes | Yes | Supported by design |
| 209FD-R | | MPEG4 M-JEPG | 1 | 640x480 | No | 0/0 | No | Yes | Yes | Supported by design |
| 209MFD | | MPEG4 M-JEPG | 1 | 1280x1024 | No | 0/0 | Yes | Yes | Yes | Supported by design |
| 209MFD-R | | MPEG4 M-JEPG | 1 | 1280x1024 | No | 0/0 | Yes | Yes | Yes | Supported by design |
| 210 | | MPEG4 M-JEPG | 1 | 640x480 | No | 1/1 | | Yes | Yes | Supported by design |
| 210A | 4.40 | MPEG4 M-JEPG | 1 | 640x480 | One-way | 1/1 | No | Yes | Yes | |
| 211 | | MPEG4 M-JEPG | 1 | 640x480 | No | 1/1 | No | Yes | Yes | Supported by design |
| 211A | | MPEG4 M-JEPG | 1 | 640x480 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| 211M | | MPEG4 M-JEPG | 1 | 1280x1024 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| 211W | | MPEG4 M-JEPG | 1 | 640x480 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| 212 | | MPEG4 M-JEPG | 1 | 640x480 | One-way | 1/1 | Yes | Yes | Yes | Supported by design |
| 213 | | MPEG4 M-JEPG | 1 | 704x576 | One-way | 2/3 | Yes | Yes | Yes | Supported by design |
| 214 | 4.33 | MPEG4 | 1 | 704x480 | One-way | 1/1 | Yes | Yes | Yes | |

| | | | | | | | | | | |
|----------|--|--------------------------|---|-----------|---------|-----|-----|-----|-----|------------------------|
| | | M-JPEG | | | | | | | | |
| 215 | | MPEG4 M-JPEG | 1 | 704x576 | One-way | 1/1 | Yes | Yes | Yes | Supported by design |
| 216FD | | MPEG4 M-JPEG | 1 | 640x480 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| 216FD-V | | MPEG4 M-JPEG | 1 | 640x480 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| 216MFD | | MPEG4 M-JPEG | 1 | 1280x1024 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| 216MFD-V | | MPEG4 M-JPEG | 1 | 1280x1024 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| 221 | | MPEG4 M-JPEG | 1 | 640x480 | No | 2/1 | No | Yes | Yes | Supported by design |
| 223M | | MPEG4 M-JPEG | 1 | 1600x1200 | One-way | 2/1 | No | Yes | Yes | Supported by design |
| 225FD | | MPEG4 M-JPEG | 1 | 640x480 | No | 2/1 | No | Yes | Yes | Supported by design |
| 231D | | MPEG4 M-JPEG | 1 | 704x576 | No | 4/4 | Yes | Yes | Yes | Supported by design |
| 232D | | MPEG4 M-JPEG | 1 | 704x576 | No | 4/4 | Yes | Yes | Yes | Supported by design |
| 233D | | MPEG4 M-JPEG | 1 | 704x576 | One-way | 4/4 | Yes | Yes | Yes | Supported by design |
| 240Q | | M-JPEG | 4 | 704x576 | No | 4/4 | No | Yes | Yes | Supported by design |
| 241Q | | MPEG4 M-JPEG | 4 | 704x576 | No | 4/4 | No | Yes | Yes | Supported by design |
| 241QA | 4.30 | MPEG4 M-JPEG | 4 | 704x576 | One-way | 4/4 | No | Yes | Yes | |
| 241S | | MPEG4 M-JPEG | 1 | 704x576 | No | 4/4 | No | Yes | Yes | Supported by design |
| 241SA | | MPEG4 M-JPEG | 1 | 704x576 | One-way | 4/4 | No | Yes | Yes | Supported by design |
| 242S | | MPEG4 M-JPEG | 1 | 704x576 | No | 4/4 | No | Yes | Yes | Supported by design |
| 243Q | | MPEG4 M-JPEG | 1 | 704x576 | No | 1/1 | No | Yes | Yes | Supported by design |
| 243SA | | MPEG4 M-JPEG | 1 | 704x576 | One-way | 4/4 | No | Yes | Yes | Supported by design |
| 247S | | MPEG4 M-JPEG | 1 | 704x576 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| M1011 | 5.00 | MPEG4 M-JPEG H.264 | 1 | 640x480 | No | 0/0 | No | Yes | Yes | |
| M1011-W | 5.00 | MPEG4 M-JPEG H.264 | 1 | 640x480 | No | 0/0 | No | Yes | Yes | |
| M1031-W | 5.00 | MPEG4 M-JPEG H.264 | 1 | 640x480 | No | 0/0 | No | Yes | Yes | |
| M3011 | 5.00 | MPEG4 M-JPEG H.264 | 1 | 640x480 | No | 0/0 | No | Yes | Yes | Supported by design |
| P3301 | 5.01 | M-JPEG H.264 | 1 | 640x480 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| P3301-V | | M-JPEG H.264 | 1 | 640x480 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| Q1755 | 5.02 | M-JPEG H.264 | 1 | 1920x1080 | No | 1/1 | Yes | Yes | Yes | |
| Note: | M-JPEG: Due to the HW constraints, the frame rate and audio will be impacted if resolution and quality are high. | | | | | | | | | |
| Q7401 | | M-JPEG H.264 | 1 | 704x576 | One-way | 2/2 | Yes | Yes | Yes | Supported by design |
| Q7406 | | M-JPEG H.264 | 6 | 704x576 | No | 1/1 | Yes | Yes | Yes | Supported by design |

Cisco



| Device Name | Tested Firmware | Video Format | Video Channels | Max Resolution | Audio | I/O Channels | PTZ Support | Motion Detection | UPnP | Remarks |
|----------------|-----------------|-----------------|----------------|----------------|---------|--------------|-------------|------------------|------|-----------|
| CIVS-IPC-2500 | V1.1.3R15 | MPEG4 M-JPEG | 1 | 720x480 | One-way | 2/2 | No | No | Yes | |
| CIVS-IPC-2500W | V1.1.3R03 | MPEG4 M-JPEG | 1 | 720x480 | One-way | 2/2 | Yes | No | Yes | |
| PVC-300 | 1.0.0 | MPEG4 | 1 | 640x480 | One-way | 1/1 | Yes | Yes | Yes | Supported |

| | | | | | | | | | | |
|-------|--|--------|--|--|--|--|--|--|--|-----------|
| | | M-JPEG | | | | | | | | by design |
| Note: | PTZ is only supported by external RS-485 device. | | | | | | | | | |

IQinVision



| Device Name | Tested Firmware | Video Format | Video Channels | Max Resolution | Audio | I/O Channels | PTZ Support | Motion Detection | UPnP | Remarks |
|-------------|-----------------|--------------|----------------|----------------|-------|--------------|-------------|------------------|------|---------------------|
| IQ042S | V3.0/2 | M-JPEG | 1 | 1280x1024 | No | 0/0 | No | Yes | No | |
| IQA25S | V2.9/6 | M-JPEG | 1 | 1280x1024 | No | 4/4 | No | No | No | |
| IQeye301 | | M-JPEG | 1 | 1280x1024 | No | 1/1 | No | Yes | No | Supported by design |
| IQeye301m | | M-JPEG | 1 | 1280x1024 | No | 1/1 | No | Yes | No | Supported by design |
| IQeye301w | | M-JPEG | 1 | 1280x1024 | No | 1/1 | No | Yes | No | Supported by design |
| IQeye302 | | M-JPEG | 1 | 1280x1024 | No | 1/1 | No | Yes | No | Supported by design |
| IQeye302w | | M-JPEG | 1 | 1280x1024 | No | 1/1 | No | Yes | No | Supported by design |
| IQeye303 | | M-JPEG | 1 | 1280x1024 | No | 1/1 | No | Yes | No | Supported by design |
| IQeye303w | | M-JPEG | 1 | 1280x1024 | No | 1/1 | No | Yes | No | Supported by design |
| IQeye501 | | M-JPEG | 1 | 1280x1024 | No | 1/1 | No | Yes | No | |
| IQeye510 | B2.8/608 | M-JPEG | 1 | 752x480 | No | 0/0 | No | Yes | No | |
| IQeye511 | V2.8/6 | M-JPEG | 1 | 1280x1024 | No | 0/0 | No | Yes | No | |
| IQeye601 | | M-JPEG | 1 | 1280x1024 | No | 1/1 | No | Yes | No | Supported by design |
| IQeye602 | | M-JPEG | 1 | 1280x1024 | No | 1/1 | No | Yes | No | Supported by design |
| IQeye603 | | M-JPEG | 1 | 1280x1024 | No | 1/1 | No | Yes | No | Supported by design |
| IQeye701 | V2.8/6 | M-JPEG | 1 | 1280x1024 | No | 1/1 | No | Yes | No | |
| IQeye702 | V2.8/6 | M-JPEG | 1 | 1600x1200 | No | 1/1 | No | Yes | No | |
| IQeye703 | V2.8/6 | M-JPEG | 1 | 2048x1536 | No | 1/1 | No | Yes | No | |
| IQeye705 | V2.8/6 | M-JPEG | 1 | 2560x1920 | No | 1/1 | No | Yes | No | |
| IQeye751 | | M-JPEG | 1 | 1280x1024 | No | 1/1 | No | Yes | No | Supported by design |
| IQeye752 | V2.8/6 | M-JPEG | 1 | 1600x1200 | No | 1/1 | No | Yes | No | |
| IQeye753 | | M-JPEG | 1 | 2048x1536 | No | 1/1 | No | Yes | No | Supported by design |
| IQeye755 | V2.8/6 | M-JPEG | 1 | 2560x1920 | No | 1/1 | No | Yes | No | |
| IQeye855 | V2.8/6 | M-JPEG | 1 | 2560x1920 | No | 1/1 | No | Yes | No | |

Mobotix



| Device Name | Tested Firmware | Video Format | Video Channels | Max Resolution | Audio | I/O Channels | PTZ Support | Motion Detection | UPnP | Remark |
|-------------|-----------------|-----------------|----------------|----------------|-------|--------------|-------------|------------------|------|---------------------|
| D12D-IT | | M-JPEG MxPEG | 1 | 640x480 | No | 0/0 | No | Yes | No | Supported by design |
| D12D-Sec | | M-JPEG MxPEG | 1 | 2048x1536 | No | 0/0 | No | Yes | No | Supported by design |
| D22M-Basic | | M-JPEG MxPEG | 1 | 640x480 | No | 0/0 | No | Yes | No | Supported by design |
| D22M-IT | MX-V3.4.0.9 | M-JPEG MxPEG | 1 | 640x480 | No | 0/0 | No | Yes | No | Supported by design |
| D22M-Sec | | M-JPEG MxPEG | 1 | 2048x1536 | No | 0/0 | No | Yes | No | Supported by design |
| M10D | M10-V2.2.2.17 | MJPEG | 1 | 2048x1536 | No | 0/0 | No | Yes | No | |
| M12D-IT | | M-JPEG MxPEG | 1 | 640x480 | No | 0/0 | No | Yes | No | Supported by design |
| M12D-Sec | MX-V3.4.0.9 | M-JPEG MxPEG | 1 | 2048x1536 | No | 0/0 | No | Yes | No | |
| M12D-Web | | M-JPEG MxPEG | 1 | 2048x1536 | No | 0/0 | No | Yes | No | Supported by design |
| M22M-IT | | M-JPEG MxPEG | 1 | 640x480 | No | 0/0 | No | Yes | No | Supported by design |
| M22M-Sec | | M-JPEG MxPEG | 1 | 2048x1536 | No | 0/0 | No | Yes | No | Supported by design |

| | | | | | | | | | | |
|------------|------------------|-----------------|---|-----------|----|-----|----|-----|----|------------------------|
| Q22M-Basic | | M-JPEG MxPEG | 1 | 640x480 | No | 0/0 | No | Yes | No | Supported by design |
| Q22M-Sec | MX- V3.4.5.10 | M-JPEG MxPEG | 1 | 2048x1536 | No | 0/0 | No | Yes | No | Supported by design |

Panasonic



PCC

| Device Name | Tested Firmware | Video Format | Video Channels | Max Resolution | Audio | I/O Channels | PTZ Support | Motion Detection | UPnP | Remarks |
|----------------|--|-----------------|----------------|----------------|---------|--------------|-------------|------------------|------|------------------------|
| BB-HCE481 | | M-JPEG | 1 | 640x480 | One-way | 2/1 | No | Yes | Yes | Supported by design |
| BB-HCM100 | 1.3 | M-JPEG | 1 | 640x480 | One-way | 2/1 | No | Yes | Yes | |
| BB-HCM110 | 1.3 | M-JPEG | 1 | 640x480 | One-way | 2/1 | Yes | Yes | Yes | |
| BB-HCM311 | | M-JPEG | 1 | 640x480 | One-way | 2/1 | Yes | Yes | Yes | Supported by design |
| BB-HCM331 | 1.3 | M-JPEG | 1 | 640x480 | No | 2/1 | Yes | Yes | Yes | |
| BB-HCM371 | | M-JPEG | 1 | 640x480 | One-way | 2/1 | No | Yes | Yes | Supported by design |
| BB-HCM381 | 1.3 | M-JPEG | 1 | 640x480 | No | 1/1 | Yes | Yes | Yes | |
| BB-HCM403 | | M-JPEG | 1 | 640x480 | One-way | 2/1 | No | Yes | Yes | Supported by design |
| BB-HCM511 | 1.3 | MPEG4 M-JPEG | 1 | 640x480 | One-way | 2/1 | Yes | Yes | Yes | |
| BB-HCM515 | 3.11R01 | MPEG4 M-JPEG | 1 | 1280x1024 | One-way | 2/1 | No | Yes | Yes | |
| Note: | No audio support in M-JPEG format @ 1280x1024. | | | | | | | | | |
| BB-HCM527 | | MPEG4 M-JPEG | 1 | 640x480 | One-way | 2/1 | No | Yes | Yes | Supported by design |
| BB-HCM531 | 3.51R00 | MPEG4 M-JPEG | 1 | 640x480 | One-way | 2/1 | No | Yes | Yes | |
| BB-HCM580 | | MPEG4 M-JPEG | 1 | 640x480 | No | 2/1 | No | Yes | Yes | Supported by design |
| BB-HCM581 | 1.3 | MPEG4 M-JPEG | 1 | 640x480 | One-way | 2/1 | Yes | Yes | Yes | |
| BB-HCS301 | | M-JPEG | 1 | 640x480 | One-way | 1/1 | No | Yes | Yes | Supported by design |
| BL-C1 | | M-JPEG | 1 | 640x480 | No | 0/0 | No | No | Yes | Supported by design |
| BL-C10 | | M-JPEG | 1 | 640x480 | No | 0/0 | Yes | No | Yes | Supported by design |
| BL-C111 | 3.10R01 | MPEG4 M-JPEG | 1 | 640x480 | One-way | 0/0 | Yes | No | Yes | |
| BL-C131 | | MPEG4 M-JPEG | 1 | 640x480 | One-way | 0/0 | No | No | Yes | Supported by design |
| BL-C20 | | M-JPEG | 1 | 640x480 | No | 0/0 | No | No | Yes | Supported by design |
| BL-C30 | | M-JPEG | 1 | 640x480 | No | 0/0 | Yes | No | Yes | Supported by design |
| KX-HCM110 | | M-JPEG | 1 | 640x480 | One-way | 2/1 | No | Yes | Yes | Supported by design |
| KX-HCM280 A | | M-JPEG | 1 | 640x480 | No | 2/1 | No | Yes | Yes | Supported by design |

SONY



| Device Name | Tested Firmware | Video Format | Video Channels | Max Resolution | Audio | I/O Channels | PTZ Support | Motion Detection | UPnP | Remarks |
|-------------|-----------------|-----------------|----------------|----------------|---------|--------------|-------------|------------------|------|------------------------|
| SNC-CM120 | 1.00 | MPEG4 M-JPEG | 1 | 1280x960 | One-way | 1/2 | Yes | Yes | No | |
| SNC-CS10 | | MPEG4 M-JPEG | 1 | 640x480 | One-way | 1/1 | No | Yes | No | Supported by design |
| SNC-CS11 | 1.05 | MPEG4 M-JPEG | 1 | 640x480 | One-way | 1/1 | No | Yes | No | |
| SNC-CS20 | | MPEG4 M-JPEG | 1 | 768x576 | One-way | 1/2 | No | Yes | No | Supported by design |
| SNC-CS3 | | M-JPEG | 1 | 736x480 | No | 1/2 | No | No | No | Supported by design |
| SNC-CS50 | 2.21 | MPEG4 M-JPEG | 1 | 640x480 | One-way | 2/2 | No | Yes | No | |
| SNC-DF40 | 1.17 | MPEG4 | 1 | 640x480 | One-way | 1/2 | No | Yes | No | |

| | | | | | | | | | | | |
|-----------|-------------------------|--------------------------|---|----------|---------|-----|-----|-----|----|------------------------|--|
| | | M-JPEG | | | | | | | | | |
| SNC-DF50 | 1.11 | MPEG4 M-JPEG H.264 | 1 | 640x480 | One-way | 1/2 | No | Yes | No | | |
| SNC-DF70 | 1.17 | MPEG4 M-JPEG | 1 | 640x480 | One-way | 1/2 | No | Yes | No | | |
| SNC-DF80 | 1.11 | MPEG4 M-JPEG H.264 | 1 | 640x480 | One-way | 1/2 | Yes | Yes | No | | |
| SNC-DM110 | | MPEG4 M-JPEG | 1 | 1280x960 | One-way | 1/2 | No | Yes | No | Supported by design | |
| SNC-DM160 | 1.01 | MPEG4 M-JPEG | 1 | 1280x960 | One-way | 1/2 | Yes | Yes | No | | |
| SNC-DS10 | 1.01 | MPEG4 M-JPEG H.264 | 1 | 768x576 | One-way | 1/2 | No | Yes | No | | |
| SNC-DS60 | 1.00 | MPEG4 M-JPEG | 1 | 640x480 | One-way | 1/2 | No | Yes | No | | |
| SNC-P1 | 1.28 | MPEG4 M-JPEG | 1 | 640x480 | One-way | 1/1 | No | Yes | No | | |
| SNC-P5 | 1.11 | MPEG4 M-JPEG | 1 | 640x480 | One-way | 2/1 | Yes | Yes | No | | |
| SNC-RX530 | 3.00 | MPEG4 M-JPEG H.264 | 1 | 640x480 | One-way | 2/2 | Yes | Yes | No | | |
| SNC-RX550 | | MPEG4 M-JPEG H.264 | 1 | 640x480 | One-way | 2/2 | Yes | Yes | No | Supported by design | |
| SNC-RX570 | 3.01 | MPEG4 M-JPEG H.264 | 1 | 640x480 | One-way | 2/2 | Yes | Yes | No | | |
| SNC-RZ25 | 1.29 | MPEG4 M-JPEG | 1 | 640x480 | One-way | 2/2 | Yes | Yes | No | | |
| SNC-RZ30 | 3.14 | M-JPEG | 1 | 736x480 | One-way | 3/2 | Yes | No | No | | |
| SNC-RZ50 | 2.21 | MPEG4 M-JPEG H.264 | 1 | 640x480 | One-way | 2/2 | Yes | Yes | No | | |
| SNC-Z20 | 1.06 | M-JPEG | 1 | 736x480 | No | 1/2 | Yes | No | No | | |
| Note: | PTZ Support: zoom only. | | | | | | | | | | |
| SNT-V704 | 2.15 | MPEG4 M-JPEG | 4 | 720x480 | One-way | 1/4 | No | No | No | | |