

AX3000 Wi-Fi 6 Range Extender

SE30**Wi-Fi
6**

Expand Your Wi-Fi Coverage

- Wi-Fi 6 technology provides faster speeds, greater capacity, and less network congestion
- Superior Wi-Fi 6 performance with speeds of up to 2,976 Mbps¹ for 4K video streaming, gaming, and file transfers
- Dual-band (2.4 GHz/ 5 GHz) Wi-Fi with MU-MIMO technology enhances Wi-Fi throughput
- One Gigabit Ethernet LAN port for high-speed wired connectivity
- Works with any existing Wi-Fi router or gateway regardless of brand
- The latest WPA3 encryption provides the highest level of network protection
- Compliant with EN 18031 security enhancements to meet the EU Radio Equipment Directive (RED) cybersecurity requirements
- Free D-Link SetupGo App for easy setup



Wi-Fi 6 Technology

Perfect for uninterrupted 4K streaming, online gaming, and video calls



Dual Band Connectivity

2.4 GHz and 5 GHz Wi-Fi bands for flexible connectivity



Robust Network Protection

Safeguards your network with the latest Wi-Fi security protocols and cybersecurity certifications



Wide Compatibility

Easily add Wi-Fi or expand coverage using your existing router or gateway



Signal Strength Indicator

Provides visual indication of signal strength



Easy Setup

Set up your Wi-Fi quickly with the D-Link SetupGo App

SE30

AX3000 Wi-Fi 6 Range Extender

Technical Specifications		
General		
Device Interface	• 1 x Gigabit Ethernet LAN port • 1 x Reset button • 1 x WPS button	
LED	• Power, Wi-Fi 2.4 GHz signal, Wi-Fi 5 GHz signal, Internet, WPS, LAN	
Antenna Type	• 2 x 2.4/5 GHz dual-band internal antennas	
Plug Type	• Australian 2 (or 3) Pin Wall Plug	
Wi-Fi Data Rate ^{1,2}	• 2.4 GHz up to 574 Mbps • 5 GHz up to 2,402 Mbps	
IEEE Standards	• 2.4 GHz: IEEE 802.11n/g/b • 5 GHz: IEEE 802.11ax/ac/n/a	• Ethernet: IEEE 802.3u/ab • Wi-Fi Management: IEEE 802.11k/v/h
Functionality		
Security Protocol	• WPA-Personal • WPA2-Personal	• WPA3-Personal • Wi-Fi Protected Setup (WPS)
Power Saving	• Target Wake Time (TWT)	
Protocol	• IPv4	
Operation Mode	• Bridge mode • Repeater mode	
Device Management	• D-Link SetupGo (iOS and Android™)³ • Web UI	
Physical		
Hardware Version	A1	
Dimensions	150 x 78 x 48 mm; dimensions do not include plug pins	
Weight	239.4 g	
Power Input	100 to 240 VAC, 50/60 Hz	
Max Power Consumption ¹	24W	
Operating Temperature	0°C to 40°C	
Storage Temperature	-20°C to 65°C	
Operating Humidity	10% to 90% non-condensing	
Storage Humidity	5% to 95% non-condensing	
Certifications	CE, RCM	
Ordering Information		
SE30	AX3000 Wi-Fi 6 Range Extender	
Barcode / UPC	790069483646	

1. Maximum wireless signal rate derived from IEEE Standard 802.11ax/ac/n/g/b/a specifications. Actual performance may vary due to settings, cabling, temperature, network configuration, interface, device compatibility, environmental and on-site conditions, and other similar factors. References to power capability, signal or processing speed, signal range or distance, data encryption, storage capacity, display properties, or other performance metrics are based on optimal conditions derived from industry standards and provided for informational purposes only.

2. Supported frequency bands are dependent on regional variants and may not be available in all markets.

3. Android is a trademark of Google LLC.

