

# 65W GaN Charger

**DCP-651**

## Key Features

- Ensure your devices stay charged while you're on the go with a reliable and efficient charging block
- The block's charging capability includes one USB Type-C port that delivers up to 65W of charging power
- GaN technology facilitates powerful, efficient, and safe charging with comprehensive safety protection
- A compact and convenient multi-port charging block designed to power a variety of devices while minimizing heat buildup
- The USB connectors support a wide range of power outputs, with various maximum capacities
- Designed with advanced protection features: overcurrent, overvoltage, overtemperature, overcharge, and short circuit protection
- USB PD 3.0 and QC 4.0 for fast charging
- Interchangeable power plugs for AU, EU, UK, and US to ensure smooth charging experience when you travel



## User Benefits



### Supercharged Productivity

GaN technology enables efficient and reliable charging for up to 3 devices simultaneously, ensuring you stay productive and connected wherever you are



### Fast Charging

Power your personal devices and gadgets with fast charging capabilities, thanks to standardized charging technologies



### Ultra-compact & Portable

With its sleek, rounded edge design, you can easily toss it into your bag without worrying about scratching other items



### Power Efficiency with Safety Protection

GaN technology and multifold protection enhance safety and energy efficiency, reducing electricity costs and extending product lifespan



### Universal Support


The interchangeable power plugs make it ideal for travel and remote work, capable of charging devices ranging from laptops to phones and tablets



### Best On-the-Go Partner

Satisfy your portable charging needs by charging smart and portable accessories safely and efficiently – all at the same time

# Technical Specifications

| General               |  |
|-----------------------|--|
| Power Input           | 100AC-240 V AC (MIN: 90 V, MAX: 264 V)<br>Rated frequency: 50/60Hz<br>Rated Input Current: Max 1.5A@100-240 V input & Full load  |
| Output Interfaces     | <div><ul style="list-style-type: none"><li>When only one charging port is used<ul style="list-style-type: none"><li>USB Type-C1 or C2<ul style="list-style-type: none"><li>Output: 5.0V@3.0A, 9.0V@3.0A, 12.0V@3.0A, 15.0V@3.0A, 20.0V@3.25A   MAX 65W</li><li>Output protocol: Power Delivery 3.0 (PD 3.0) and Quick Charge 4.0 (QC 4.0)</li></ul></li><li>USB Type-A<ul style="list-style-type: none"><li>Output: 4.5V@5.0A, 5.0V@4.5A, 5.0V@3A   MAX 22.5W</li><li>Output protocol: Quick Charge 3.0 (QC 3.0)</li></ul></li></ul></li><li>When more than one charging port is used<ul style="list-style-type: none"><li>USB Type-C1 &amp; C2: 45.0W &amp; 20.0W</li><li>USB Type-C1 &amp; USB Type-A: 45.0W &amp; 18.0W</li><li>USB Type-C2 &amp; USB Type-A: Total 15.0W</li></ul></li><li>Maximum Total Output: 65</li></ul></div> <div></div> |
| Protection            | <ul style="list-style-type: none"><li>Overcurrent protection</li><li>Overvoltage protection</li><li>Overcharge protection</li><li>Overtemperature protection</li><li>Short circuit protection</li></ul>  |
| Physical              |  |
| Dimensions            | 44.4 x 29.4 x 63.1 mm (1.75 x 1.16 x 2.48 in)  |
| Power Input           | MAX 1.5A@100-240 V   |
| Weight                | 240 g (8.47 oz)  |
| Operating Temperature | 0 to 40 °C (32 to 104 °F)  |
| Storage Temperature   | -20 to 80 °C (-4 to 176 °F)  |
| Operating Humidity    | 10% to 100% non-condensing   |
| Storage Humidity      | 30% to 100% non-condensing   |
| Certifications        | CE, FCC  |
| Package Contents      |  |
| DCP-651               | 65W GaN Charger<br>Interchangeable AC Plug (US,UK,EU and AU)<br>Quick Installation Guide<br>Warranty Card  |