

65W GaN Charger with USB-A and 2 USB-C ports

DCP-651

Power Up, Achieve More with 65W GaN Charger.

- Ensure your devices stay charged while you're on the go with a reliable and efficient charging block
- A compact and convenient multi-port charging block designed to power a variety of devices while minimising heat buildup
- **GaN Technology:** Facilitates powerful, efficient, and safe charging with comprehensive safety protection
- **65W Fast Charging:** Fast charging your laptop, tablet, smartphone, and more with up to PD 3.0/65W output
- **Three USB-C / USB-A Ports:** Features 2 x USB-C and 1 x USB-A ports to charge 3 devices simultaneously
- **Safety Protection:** Power supply is disabled in the errors caused by overcurrent, overvoltage, overcharge, overtemperature or short circuit
- **Interchangeable Plugs:** Supports AU, EU, UK, and US plug standards— perfect for international travel



Supercharged Productivity

GaN technology enables fast and reliable charging to 3 devices simultaneously for better productivity, anytime and anywhere



Fast Charging

Power your personal devices and office gadgets with fast charging capabilities, thanks to standardised charging technologies



Ultra-Compact & Portable

With its sleek, rounded edge design, you can easily toss it into your bag without worrying about scratching other items



Power Efficiency with Safety Protection

GaN technology and multifold protection enhance safety and energy efficiency, reducing electricity costs and extending product lifespan



Universal Support

The interchangeable power plugs make it ideal for travel and remote work, capable of charging devices ranging from laptops to phones and tablets



Best On-the-Go Partner

Satisfy your portable charging needs by charging smart and portable accessories safely and efficiently - all at the same time

65W GaN Charger with USB-A and 2 USB-C ports

Technical Specifications	
Functionality	
Power Input	110AC - 240V AC (MIN: 99V, MAX: 264V) Rated frequency: 50/60Hz Rated Input Current: Max 1.5A@100-240V input & Full load
Output Interfaces	<ul style="list-style-type: none"> When only one charging port is used <ul style="list-style-type: none"> USB Type-C1 or C2 <ul style="list-style-type: none"> Output: 5.0V@3.0A, 9.0V@3.0A, 12.0V@3.0A, 15.0V@3.0A, 20.0V@3.25A MAX 65W Output protocol: Power Delivery 3.0 (PD 3.0) and Quick Charge 4.0 (QC 4.0) USB Type-A <ul style="list-style-type: none"> Output: 4.5V@5.0A, 5.0V@4.5A, 5.0V@3A MAX 22.5W Output protocol: Quick Charge 3.0 (QC 3.0) When more than one charging port is used <ul style="list-style-type: none"> USB Type-C1 & C2: 45.0W & 20.0W USB Type-C1 & USB Type-A: 45.0W & 18.0W USB Type-C2 & USB Type-A: Total 15.0W <p>Maximum Total Output: 65W</p>
Protection	<ul style="list-style-type: none"> Overcurrent Protection Overvoltage Protection Overcharge Protection Overtemperature Protection Short Circuits Protection
Physical	
Dimensions	44.4 x 29.4 x 63.1mm
Weight	240g
Power Input	MAX 2.5A@100-240V
Operating Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 80°C
Operating Humidity	10% to 100% non-condensing
Storage Humidity	30% to 100% non-condensing
Certifications	CE, FCC, RCM
Ordering Information	
DCP-651	65W GaN Charger with USB-A and 2 USB-C ports
Barcode / UPC	790069479731

