

Document: The settings example on DI-701 with Bigpond ADSL service.  
Author: Steven Sia  
Rev: 2.0

IMPORTANT: Please click on "SAVE" after finish setting up all the tabs shown here.

Leave the "Device/Computer Name" and "Domain" as their default values.  
Check the "PPPoE Enabled" and type in your username and password given.  
Remember to add @bigpond behind your user name.

The screenshot shows a 'Configure' window with the following details:

- Window Title: Configure
- Active Tab: Management
- Firmware version: 3.21
- Device/Computer Name: Untitled
- Domain Name: Domain
- PPPoE Enabled:
- Username: user@bigpond
- Password: [masked]
- Auto-disconnect if idle for: 5 minutes
- Change Administrator's Password:
- TELNET management from Internet:
- Buttons: Save, Cancel

The image shows a 'Configure' dialog box with the following settings:

- Management
- Local Port
- Global Port
- Virtual Server
- Packet Filters

IP address: 192 . 168 . 1 . 254

SubNetmask: 255 . 255 . 255 . 0

Do not distribute IP address to local computer:

Distribute IP addresses to local computer:

Continuous IP address pool starts at: 192 . 168 . 1 . 1

Number of IP address in pool: 128


Buttons: Save, Cancel


If you already have existing IP addresses set up in your network, you might want to configure this DI-701 to be part of your network; else just leave it as defaults.


On "Global Port" tab, select "Obtain global port configuration automatically".  
Nothing is set under "Virtual Server" and "Packet Filters" tabs. Leave them as defaults.  
SAVE all the settings now by clicking on the "Save" button at the bottom.


Now, check the settings on EACH PC.

Everything in this example is left as the PC default. If you already have your IP network set up, check and configure them accordingly.










The rest are all at their default values.  
OK and Restart the PC now.

Lastly, on EACH PC's browser (eg. I.E. 5), make sure that under Tools > Internet Options > Connections tab > LAN Settings Untick everything or Tick only "Automatically detect settings"



Thank you very much for reading this setup document. If you have any further queries, please write to [support@dlink.com.au](mailto:support@dlink.com.au) with descriptions of your steps and Windows mesg shown to you.