

# DKVM-08LB

## 2U 8-port KVM Switch with Keyboard/Trackball/15" TFT Display



### FEATURES

- 8 PCs share one console with One Screen Display
- Daisy Chain port allows max. access up to 64 PCs through eight banks of KVM-08LB unit
- Hot plug function add PCs or remove connected PCs for maintenance without powering off the KVM Switch or PCs
- No DIP-switch setting needed and auto detect daisy chain bank
- On-Screen Display menu gives the user a visual interface to name and select computers
- Support eight characters password protection and search KVM Server name
- On-Screen Display, push button or keyboard "Hot Key" commands switching
- Support VGA, SVGA and MultiSync monitors
- LCD panel up to 1024x768 resolution support, 200MHz Bandwidth
- Supports both AT and PS/2 TYPE keyboards
- Status LEDs on front panel
- Microsoft IntelliMouse, Microsoft IntelliMouse Explorer support and emulation
- No software needed

### Optional

Model	Item	Quantity	Description
KVM-08CB	VGA/KB/Mouse 3 in 1 cable (180cm)	2 pcs	One D-Sub 15-pin male header and two 6-pin Mini Din male headers to one D-Sub 15 pin male header and two 6-pin Mini Din male headers
	VGA/KB/Mouse 3 in 1 cable (90cm)	1 pc	For Daisy Chain
	Mouse Conversion	4 pcs	DB-9 TO 6-PIN Mini-Din

### SPECIFICATIONS

- **Computer connections:** 8
- **Display LEDs:** 3
- **Connectors**
  - **Keyboard:** 6-pin Mini-din
  - **Mouse:** 6-pin Mini-din
  - **Monitor:** 15-pin HD DB type
- **Cascade:** 15-pin D-Sub (Daisy-Chain)
- **Cascade Port:** 1 (Daisy-Chain)
- **Cascade Level:** 8
- **On Screen Display:** Yes
- **Rackmount:** 2U 19" Rackmount
- **MAX. Access PCs:** 64
- **Menu Selection:** Yes
- **Hot Key Control:** Yes
- **Switching Confirmation:** Beeper
- **Keyboard State:** Saved and Restored
- **Keyboard + Mouse:** Industrial Level, Cherry Keyboard with trackball
- **LCD Power on/off LED:** 1
- **Display DATA Channel:** DDC1, DDC2B, DDC2AB
- **Resolution:** Support up to 1024 x 768 (Sharp)
- **Bandwidth:** 200MHz
- **Enclosure:** Metal
- **Storage (Celsius) Temperature:** -20-60°C
- **Dimension (H x W x D):** 88 x 440 x 508mm
- **Weight:** 22.1 kg
- **Power Supply:** 4A 12V Output Adapter
- **Included KVM-CB cable kit:** 1 sets. For additional quantity of KVM-CB cable kits, please contact our sales representative.