

DSL-500/504 Console Commands Index and Syntax

Commands are:

- | | | |
|---------------|-------------|--------------------------------------|
| 1. atm | [<command>] | - send command to atm process |
| 2. bridge | [<command>] | - send command to bridge process |
| 3. buffer | [<command>] | - send command to buffer process |
| 4. bun | [<command>] | - send command to bun process |
| 5. chips | [<command>] | - send command to chips process |
| 6. config | [<command>] | - send command to config process |
| 7. dhcpclient | [<command>] | - send command to dhcpclient process |
| 8. dhcpserver | [<command>] | - send command to dhcpserver process |
| 9. diap | [<command>] | - send command to diap process |
| 10. edd | [<command>] | - send command to edd process |
| 11. ethernet | [<command>] | - send command to ethernet process |
| 12. event | | - control display of events |
| 13. flashfs | [<command>] | - send command to flashfs process |
| 14. ip | [<command>] | - send command to ip process |
| 15. ip_filter | [<command>] | - send command to ip_filter process |
| 16. isfs | [<command>] | - send command to isfs process |
| 17. itex | [<command>] | - send command to itex process |
| 18. nat | [<command>] | - send command to nat process |
| 19. oam | [<command>] | - send command to oam process |
| 20. oamcli | [<command>] | - send command to oamcli process |
| 21. portcli | [<command>] | - send command to portcli process |
| 22. ppp | [<command>] | - send command to ppp process |
| 23. r1483 | [<command>] | - send command to r1483 process |
| 24. reflect | [<command>] | - send command to reflect process |
| 25. restart | | - restart system |
| 26. snmp | [<command>] | - send command to snmp process |
| 27. tftp | [<command>] | - send command to tftp process |
| 28. uptime | | - show time system has been running |
| 29. version | | - show system software version |

1. atm

info	-Get ATM driver information
pool	-Get entry, size, prefix, count, name

2. bridge

config	<command> - configuration commands
device	command - Alter bridge configuration
ethertype	[<port> "any" "ip" "pppoe"] - Set or display forwarded packet types
filter	- Display filtering database
filterage	[age] - Set or display filter age time
flush	[<port>] - Flush filtering database on port(s)
info	- Show version
interface	command - Process interface command
portfilter	[<source port> "all" <dest ports>] - Set or display ports to forward to
spanning	{command} - Control spanning tree operation
status	- Display bridge status
version	- Show version

3. buffer

list	- list the buffer pools
info	- [<name>] show [or set] current pool
show	- [<n>] show buffer <n> in current pool, or all buffers in use
steal	- <n> steal <n> buffers from current pool, (0 to reset)
version	- display version information for buffer pools

4. bun

BUN Commands -	
help [command]	- Display summary of commands

version	- Show software version
build	- Show build information
config <config_spec>	- Enter manual configuration request
list config	- Display all configuration requests
list devices	- Display registered driver devices
list ports	- Display registered ports
list channels <port_name>	- Display enabled channels on a port
list all open channels <port_name>	- Display all open channels on a port
list spices	- Display all available spices
list objects	- Display all data objects
show system	- Show system attributes
set system	- Set system attributes
show device <device_name>	- Display device information
show port <port_name>	- Display port information
show channel <port_name> <channel_number>	- Display channel information
set port <port_name> / <attribute> = <value>	- Set port attribute
set channel <portname> <channelnumber> / <attribute> = <value>	- Set channel attribute
reset port <port_name>	- Reset port hardware
list classes	- List available port classes
show class <classname>	- Show class members

Ethernet Device -

ethernet filter	- Show NP filter table
-----------------	------------------------

ADI ADSL Device -

adi supervisor	- Toggles supervisor mode on or off
adi wc <CMV> <offset> <data>	- Write a CMV
adi rc <CMV> <offset>	- Read a CMV
adi mp	- read mp message buffer
adi last fail	- Show fail code of last initialization failure
adi trace <level>	- Set ADI driver trace level
adi poll rate <rate>	- Set ADI driver interrupt poll rate (msec)

5. chips

cpu	- print percentage of cpu cycles used
debug	- enter debug process
exit	- abort from ATMos
info	- print out version information and machine's address
mem	- memory used on a process-by-process basis
stack	- stack usage on a process-by-process basis
rb	<addr> - read byte at address <addr>
rh	<addr> - read halfword at address <addr>
rw	<addr> - read word at address <addr>
tell	<process> <string> - send string to process using TELL message
wb	<addr> <val> - write byte <val> at address <addr>
wh	<addr> <val> - write halfword <val> at address <addr>
ww	<addr> <val> - write word <val> at address <addr>

6. config

list	- List all modules registered
print	[low medium high] [<module>] - Print configuration
reset	[<module>] - Reset configuration to default
save	- Save configuration
resource	[<process> [<resource> [<value>]]] - Control resources
default	- restore factory default settings
version	- Display version information

7. dhcpclient

config	- Displays client configuration file
help	- Gives help on available commands
pool	- Show DHCP client pool allocation stats
status	- Shows status of active lease, or [all] leases
trace	- Activates trace option(s)
untrace	- Deactivates trace option(s)
version	- Show software version

8. dhcpserver

config	- Displays server configuration file
help	- Gives help on available commands
pool	- Show DHCP pool allocation statistics
status	- Shows status of server leases
trace	- Activates trace option(s)
untrace	- Deactivates trace option(s)
version	- Display software version

9. diap

help	- Gives help on available commands
enable	- Enable DIAP Function
disable	- Disable DIAP Function
passwd	- Set DIAP Passwd -- passwd <password> none
status	- Show status of DIAP settings
trace	- Activates trace option(s)
untrace	- Deactivates trace option(s)
version	- Show software version

10.edd

event	[level] - set event logging level
interface	[id] command - process interface command for device id
status	- device status
version	- display driver information

11. ethernet

event	[level] - set event logging level
interface	[id] command - process interface command for device id
status	- device status
version	- display driver information

12. event

event help	- show this help
event n next	- show next part of event buffer
event p previous	- show previous part of event buffer
event r recent	- show most recent part of event buffer
event show	- enable display of events as they occur
event unshow	- disable display of events as they occur

13. flashfs

cat	<file> - show file contents
config	- display flash configuration
fsck	- file system check, checks FLASH integrity
id	<x> - display chip ID for device x
info	- display file system information
ls	[l] - list FLASHFS files [more detail]
rewrite	<file> - rewrite boot area with ISFS file <file>
trace	[level] - show/set tracing level
update	- commit ISFS files to FLASH
version	- display version number
wipe	- irreversibly erase FLASH contents

14. ip

arp syntax:

arp <cmd>	- execute arp subcommand
arp help	- list subcommands available

config syntax:

config [save]	- display config or save to flash
---------------	-----------------------------------

device syntax:

device [list]	- list interface definitions
device add <i/f> <type> <file> [mtu <size>] [<IPAddr> dhcp]	

- create interface definition

device delete <i/f>

- remove interface definition

device flush - remove all interface definitions

disable syntax:

disable [<i/f>] - prevent use of interfaces or just interface <i/f>

enable syntax:

enable [<i/f>] [mtu <size>] [<IPaddr>]

- enable use of all interfaces or interface <i/f> if given

- set <i/f> IP address to <IPaddr>

- set MTU for interface

help syntax:

help - list commands available

help all - list commands and their syntax

help <command> - list syntax for command

ipatm syntax:

ipatm <cmd> - execute ipatm subcommand

ipatm help - list subcommands available

nat syntax:

nat add <i/f> - install NAT on interface

nat delete <i/f> - uninstall NAT from interface

norelay syntax:

norelay [all | <i/f name> [<i/f name>] [forward]]

- disallow relaying between i/fs

ping syntax:

ping <host> [<ttl> [<size>]]

- request echo from <host>

relay syntax:

relay - list existing relays in place

relay all | <i/f name> [<i/f name>] [forward]

- allow relaying between i/fs

rip syntax:

- rip <sub cmd> - execute rip subcommand
- rip help - list subcommands available

route syntax:

route add <dom name> a.b.c.d <relay> [am:bm:cm:dm [<cost> [<timeout s>]]]

- define/edit an IP forwarding route

route delete <dom name>

- delete a route

route flush - delete all routes

routes syntax:

- routes - show IP forwarding routes

snmp syntax:

- snmp <sub cmd> - execute snmp subcommand
- snmp help - list subcommands available

stats syntax:

- stats <sub cmd> - execute stats subcommand
- stats help - list subcommands available

subnet syntax:

subnet add <net name> <i/f name> a.b.c.d am:bm:cm:dm

- create subnet definition

subnet delete <net name>

- remove subnet definition

subnet flush - remove all subnet definitions

version syntax:

- version - display software version no.

15.ip_filter

- add help | <command> - set up rules for filter packets

delete	help <command> - delete set or rules for filter packets
flush	help <command> - flush all setting for filter packets
list	help <command> - list setting for filter packets

16. isfs

ls	- list ISFS files
rm	<file> - remove file from ISFS
cat	<file> - show file contents
trace	[level] - show/set tracing level
version	- displays version number

17.itex

version	- display version of itex implementation
line	- Use up or down to activate/deactivate the line
rate	- Get up/down stream rates
mode	- Set mode [auto,ansi,dmt,lite]
info	- Get info
txgain	- Set/Get tx gain value
enhance	- Set enhance mode
priority	- Set priority(ansi first or g.hs first)(0:ansi,1:g.hs)
alarm	- Get Alarm indication
getes	- Get error second
getsnr	- Get snr
getrsd	- Get RSD
channelmgr	- Channel management
setcurve	- Set curve
trellis	- Set Trellis 1/0
bitswap	- Set Bitswap 1/0
dyinggasp	- Send DyingGasp
vendorid	- Set vendorid
test	- test ITeX135
delay	- ANSI delay
list	- List current configuration
minds	- Set/Get Minimum DownStream value

18. nat

event	[<level>] - show or change current event tracing level
interfaces	- list interfaces
inbound	help <command> - set up rules for inbound packets
info	- show information about configured options
protocols	- list protocols supported via ALGs
sessions	<i/f name> [summary all] - list active sessions
stats	<i/f name> [reset] - show statistics
version	- display ATMOS NAT version
dmzip	- show or set DMZ ip; Syntax: dmzip xxx.xxx.xxx.xxx

19. oam

version	- show version
config	- show configuration
trace	<util fault cc loopback all none > - show / set tracing
dl	- dump contents of lookup tables

20. oamcli

config	- display message saying there is no storable configuration
version	- show oamcli version
getversion	- get the oam process version
inf	- get a channels state
list	- list channels state
ccglobalaccept	- toggle auto acceptance/rejection of CC activate requests
pmglobalaccept	- toggle auto acceptance/rejection of PM activate requests
segmentset	<port> <vpi> <vci> <flags> - set up a segment sink point
segmentclear	<port> <vpi> <vci> <flags> - remove a segment sink point
faultset	<port> <vpi> <vci> <flags> - turn fault management on
faultclear	<port> <vpi> <vci> <flags> - turn fault management off
faultwatch	<port> <vpi> <vci> <flags> - turn fault monitoring on
faultunwatch	<port> <vpi> <vci> <flags> - turn fault monitoring off

faultbegin	<port> <vpi> <vci> <flags>	- declare a fault state
faultend	<port> <vpi> <vci> <flags>	- clear a fault state
ccset	<port> <vpi> <vci> <flags>	- set up reception of activation requests
ccclear	<port> <vpi> <vci> <flags>	- clear reception of activation requests
ccsetauto	<port> <vpi> <vci> <flags>	- set up auto accept of activation requests
ccactivate	<port> <vpi> <vci> <flags> <dir>	- send activate request
ccdeactivate	<port> <vpi> <vci> <flags> <dir>	- send deactivate request
ccstart	<port> <vpi> <vci> <flags> <dir>	- start transmission/reception of CC cells
ccstop	<port> <vpi> <vci> <flags> <dir>	- stop transmission/reception of CC cells
loopset	<port> <vpi> <vci> <flags> <llid>	- enable loopback
loopclear	<port> <vpi> <vci> <flags>	- disable loopback
loop	<port> <vpi> <vci> <flags> <llid>	- send a loopback cell
loopstats	<port> <vpi> <vci> <flags>	- display loopback stats
pmset	<port> <vpi> <vci> <flags>	- set up reception of activation requests
pmclear	<port> <vpi> <vci> <flags>	- clear reception of activation requests
pmsetauto	<port> <vpi> <vci> <flags>	- set up auto accept of activation requests
pmactivate	<port> <vpi> <vci> <flags> <txblock> <rxblock> <dir>	- send activate request
pmdeactivate	<port> <vpi> <vci> <flags>	- send deactivate request
pmstart	<port> <vpi> <vci> <flags> <txblock> <rxblock> <dir>	- start transmission/reception of PM cells
pmstop	<port> <vpi> <vci> <flags> <dir>	- stop transmission/reception of PM cells
pmstats	<port> <vpi> <vci> <flags>	- display PM stats

21. portcli

8khzsource [<port> [int|off]] - set source of 8kHz reference signal

errors [diff]	- show error counts
help [all <command>]	- print help information
portinfo [<port>]	- show port information
portload [<port>]	- show port loading
portmode <port> all uni30 uni31 uni40 iispuser iispnet mast gsmp ifmp	- set port mode (group of flags)
setportflag <port> all <portflag>	- set port flag
show <port>	- show detail information for a port
speed <port> [tx default <cps>][rx default cps]	- set port speed
stats [diff]	- print statistics
unsetportflag <port> all <portflag>	- clear port flag
version	- show switch CLI version
vport	- add or remove virtual ports

22. ppp

bcpr	- <channel> bcpr stp nostp: set if BCP uses spanning tree packets over this channel
clear	- <channel> clear: clear channel to initial state
disable	- <channel> disable: disable PPP on this channel
discard	- <channel> discard [<size>]: send LCP 'discard' packet
echo	- <channel> echo [<size>]: send LCP 'echo' packet
enable	- <channel> enable [pppoe]: enable this channel with current settings in either pppoa or pppoe encapsulation
event	- event [<1-5>]: set/read current event report level
hdlc	- <channel> hdlc [1 0]: set HDLC headers on this channel
info	- <channel> info [all]: show information about this channel
interface	- <channel> interface <n>:

	attach channel to specified interface
	interface <n> localip <ipaddr>: set local IP address on specified interface
	interface <n> stats show statistics on specified interface
lcpmaxconfigure	- <channel> lcpmaxconfigure [<n>]: set/read current LCP Max Configure setting
lcpmaxfailure	- <channel> lcpmaxfailure [<n>]: set/read current LCP Max Fail setting
lcpmaxterminate	- <channel> lcpmaxterminate [<n>]: set/read current LCP Max Terminate setting
llc	- <channel> llc [1 0]: set LLC headers on this channel
ports	- ports: display the available port names
pvc	- <channel> pvc [[[<port>] <vpi>] <vci>] [ip mac] [listen]: set PVC details for this channel
qos	- <channel> qos [cbr ubr] [pcr <pcr-tx> [<pcr-rx>]]: set QoS details for this channel
remoteip	- <channel> remoteip <ipaddr>: set IP address for dial-in to this channel
svc	- <channel> svc [listen addr <addr>] [ip mac]: set SVC details for this channel
theylogin	- <channel> theylogin [pap chap none]: set login required to this channel
tunnel	- <channel> tunnel <n> pptp l2tp in out: associate <channel> with tunnel number <n>
user	- user: list all user settings user add <name> pwd <passwd> [pap chap]: create new user setting user delete <name> all: delete user setting or all settings
version	- display version information for PPP
weloin	- <channel> weloin none <name> <password> [pap chap]: set our login details over this channel

ondemand	- <channel> ondemand disable enable [idle_secs]: set pppoe connect-on-demand and idle seconds before drop over this channel
r2516	- <channel> r2516 <service name> <ac name> : set pppoe service name and ac name over this channel

23. r1483

event	[level] - set event logging level
info	- display driver information
interface	command - process interface command
pvc	[none [<vpi>/<vci> [pcr <pcr>]] [<port>] - set PVC
status	- device status

24. reflect

version	- display the module version number
list	- list configured reflectors with index numbers
new	<filename> [filename] - create new reflector using specified file
delete	<index> all - delete specified reflector or all reflectors

25. restart

restart	- restart system
---------	------------------

26. snmp

access syntax:

snmp access [read write] <community> [<IP addr>]	- allow read-only or read-write access
snmp access delete <community> [<IP addr>]	- revoke specified access
snmp access flush	- revoke all access

snmp access list - list allowed access

config syntax:

config [save] - display config or save to flash

trap syntax:

snmp trap add <community> <IP addr> [<port>] - add a trap destination

snmp trap delete <community> <IP addr> [<port>]

- delete a trap destination

snmp trap flush - delete all trap destinations

snmp trap list - list trap destinations

version syntax:

version - display version information

27. tftp

list - list active tftp connections

version - displays version and trace status

connect <addr | hostname> - set IP address or host for transfers

get get <file> [<local file>] - get file from remote host

put put <file> [remote file] - put file onto remote host

trace [+flag][-flag][-*][help] - set trace options

28. uptime

uptime - show time system has been running

29. version

version - show system software version