

14-in-1 Thunderbolt 4 Docking Station

(DUF-E01)

Key Features

- Enhance your at-home workforce with a USB docking station to take the multi-tasking capability of your workstation to a new level
- The Power Button switches on and off all the ports at once
- High-quality display outputs HDMI 2.1, DP 1.4, and Thunderbolt 4 ports support screen extension or mirroring with triple display
- The aluminum alloy case combined with its detachable base improves heat dissipation
- The blazingly fast transfer speed of 40 Gbps¹ of the Thunderbolt port supports a wide range of accessories, including extrenal storage and recording devices
- Charge your latptop with up to 60W directly through the Thunderbolt 4 port
- The 3.5mm combo audio jack supports audio output and microphone input
- The Gigabit Ethernet provides high-speed, reliable wired connectivity
- The SD and microSD card slots comply with SD 3.0 to support SD cards with a capacity of up to 2 TB each





User Benefits



Maximized Work Productivity

The consolidated connectivity answers your demand of any kind of connectivity through a single Thunderbolt 4 port connection



Superior Multimedia Experience

Multiple displays provide immersive experience with 8K true-to-life visuals during content creation and gameplay



Clutter-free Desk

The all-in-one docking station connects to a host of devices and accessories to ease data accessibility production and data-intensive for seamless gaming and streaming experiences



Space Efficiency

Stand upright and can be placed anywhere with the included base stand, delivering cleaner desktop space



Time Efficiency

boosts productivity in video workflows, effortlessly managing multiple projects across several monitors



Fast Charging

Keep your devices fully charged with the simultaneous 60W and 15W power supplies while you work, eliminating downtime



Streamlined Workflow

Thunderbolt 4's exceptional bandwidth The variety of the connectors make it ideal for any workloads and optimal for multitasking in video editing or media streaming



Best Work-at-home Partner

This powerhouse of connectivity streamlines the connectivity of all your needs for business and personal uses, no matter your profession and work style

Technical Specifications

General	
Device Interfaces ¹	Video Ports: • 1 x HDMI 2.1 (7680x4320@30Hz) • 1x DP 1.4 (7680x4320@30Hz) • 1x Thunderbolt 4 (multi-functional connector)
	Network Port: • 1 x RJ45 (10/100/1000 Base-T)
	 USB & Thunderbolt Ports: Thunderbolt 4: 40 Gbps with 15W (5V@3A) power output (multi-functional connector) 1x USB Type-C 3.1 (10 Gbps) 2x USB Type-A 3.1 (10 Gbps) 1x USB Type-A 3.0 (5 Gbps) 2 x USB Type-A 2.0 (480 Mbps)
	 Memory Card Slots: SD & microSD card slots: UHS - II ; supports capacity range: 32 GB to 2 TB
	Audio Connector: • 3.5mm combo audio jack: supports left/right channel and microphone
	 Host Connector: Thunderbolt 4 (60W): 40 Gbps with USB Power Delivery (PD 3.0) for fast charge of 60W (compatible with USB 4.0)
Display Resolution ²	HDMI 2.1: 8K (7680x4320@30Hz) for single display or 4K (3840 x2160@60Hz) for dual display and triple display
	DP 1.4: 8K (7680x4320@30Hz) for single display or 4K (3840x2160@60Hz) for dual display and triple display
	Thunderbolt 4: 8K (7680x4320@30Hz) for single display or 4K (3840x2160@60Hz) for dual display and triple display
Requirements	
Operating System	macOS, Windows 10, Windows 11, and Android
Physical	
Maximum Power Consumption (W)	Power adapter 135 W (24V/5.63A)
Dimensions	188 x 40 x 125 mm (7.4 x 1.57 x 4.92 in)
Weight	1.2 Kg (2.65 lb)
Operating Temperature	0 to 40 °C (32 to 104 °F)
Storage Temperature	-20 to 65° C (-4 to 149° F)
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Certifications	FCC CE
Package Contents	
DUF-E01	14-in-1 Thunderbolt 4 Docking Station Thunderbolt 4 cable (50 cm) AC Adapter Quick Installation Guide Warranty Card

1. Speed may vary due to the hardware, software and usage of both ends.

2. Resolutions based on DP 1.4 of the input signal of the connected device. If the input signal of the connected device is compatible with DP 1.2, only 4K (3840 x2160@60H) can be supported as the max resolution for all three video interfaces (i.e. USB Type-C, DP port 1 & 2) in single, dual, and triple display configuration.

