D-Link[®]

DWM-314-G

5G Multi-Connect Dual SIM M2M VPN Router









Key Features:



Leverage flexible 4G/5G dual-mode compatibility to adapt seamlessly to diverse carrier networks.



Dual-SIM Failover

Two SIM slots with auto-failover redundancy to ensure uninterrupted cellular WAN connectivity.



Multi-Port GbE Connectivity

Four GbF LAN ports to connect multiple devices for mission-critical M2M applications.



Corrosion-resistant zinc-plated steel casing and robust design ensure reliable operation in harsh environments.



Secure VPN Connectivity

Protect sensitive data transmission via secure VPN tunnel to prevent unauthorised network access.



Centralised Management

Conveniently manage devices from anywhere via the D-ECS management platform.

The D-Link DWM-314-G 5G Multi-Connect Dual SIM M2M VPN Router provides 5G-NR and 4G-LTE dual-mode connectivity. It also features four Gigabit Ethernet ports for connectivity extension to meet M2M application requirements.

Unleash 5G Power for Superior M2M Connectivity


The DWM-314-G 5G Multi-Connect Dual SIM M2M VPN Router harnesses 5G technology to accelerate speeds, reduce latency, and ensure reliable connectivity with its automatic failover feature, enhancing machine-to-machine communication. Ideal for smart parking solutions, pop-up kiosks and ATM's, this 5G Multi-Connect Modem supports real-time data transfer and remote management. With 4 built-in Gigabit Ethernet ports, the DWM-314-G solution allows multiple devices to simultaneously connect without the need for an additional switch, making it perfect for space constrained environments. Additionally, secure VPN capabilities safeguard data transmission, ensuring robust security for all connected devices.

Plug & Play for Easy Installation


Designed for instant setup, the DWM-314-G offers real-time remote access and uninterrupted connectivity over long distances. Equipped with Dual SIM slots, simply insert two Micro-SIM cards (3FF) for a reliable connection to the high-speed 5G network with seamless 4G/5G switching and for failover redundancy, even if one carrier network is down. Convenient wall and DIN-rail mounting options allow the DWM-314-G to be mounted virtually anywhere. This plug-and-play Modem is perfect for small-scale deployments, ensuring robust service even in challenging environments.

Robust Build Quality

The industrial-grade casing provides reliable high-speed connectivity in extreme conditions. The corrosion-resistant zinc-plated steel case with wide operating temperature range and humidity tolerance mean that the DWM-314-G is ready for the most demanding M2M applications in virtually any environment.



5G Multi-Connect Dual SIM M2M VPN Router



Technical Specifications		
General		
Device Interfaces	 Cellular Module: 5G/4G 3GPP Rel. 16 Cellular Standards: 5G NR (Sub-6GHz), 4G LTE (DL Cat.19/UL Cat.18) SIM Slot: 2 x SIM (3FF Micro) 	 Ethernet: 4 x LAN GE Power Input: DC 9-36V (TB)(2-pin) Antenna Connector: 4 x SMA(F)-Cellular
Performance ¹	Maximum Cellular Data Throughput: 5G NSA: 3.4 Gbps (DL) / 550Mbps (UL) 5G SA: 2.4 Gbps (DL) / 900Mbps (UL) LTE: 1.6 Gbps (DL) / 200Mbps (UL)	
WAN	• Cellular: NAT	Network Monitor: ICMP Checking
Network	DHCP: DHCP ServerPort Forward: Virtual ServerDDNS: DynDNS, No-IP, Dynamic DO	• Routing: Static route, Routing information • IPv4/v6
Security	VPN Tunnel: OpenVPN, WireGuard	VPN Usage: Client mode
Firewall	• Firewall: IPS, Block WAN Ping	Access Control: Packet Filter, MAC Control
Administration	 Configuration: Web UI, Command Script, SSH Management: D-Link D-ECS² System: FW Upgrade, Reboot & Reset, System Time, NTP Service, System Log 	 Scheduling: reboot rule policy, working day SMS Service: SMS Inbox, SMS Event Management Cellular Data Capacity: Warning ratio to send SMS
Status	 Cellular Mobile: Cellular Modem Information/Status, Cellular Network Status, Cellular Signal Quality, Data Usage 	 Network Status: Connection information, Cellular Signal Quality Security: VPN Status Client: Client List
Physical		
Dimensions	131 x 99 x 40mm	
Operating Temperature	-30 to 70°C	
Storage Temperature	-40 to 85°C	
Operating Humidity	10% to 95% non-condensing	
Storage Humidity	0% to 95% non-condensing	
Other		
Certifications	CE, UKCA, RCM	
Ordering Information		
DWM-314-G	5G Multi-Connect Dual SIM M2M VPN Router	
Barcode / UPC	790069475252	

 $^{^1}$ Data rates are theoretical. Data transfer rate depends on network capacity and signal strength. 2 D-ECS License fees will apply.



